

## Selection Guide

# Sivoia® QS Triathlon® WIDR Roller Shades

Residence: \_\_\_\_\_ Room: \_\_\_\_\_ Window(s): \_\_\_\_\_


### Step 1 Select Shade Options

#### With fabric-wrapped fascia




**Regular Roll**  
fabric closest  
to the glass  
(reverse roll not  
available with fascia)

#### Headrail without fascia



**Regular Roll**  
fabric closest  
to the glass  
(standard)



**Reverse Roll**  
fabric farthest  
from the glass.  
Recommended  
to clear door or  
window hardware.

### Step 2 Select Power

#### Battery-powered



#### Plug-in



#### Power Panel



### Step 3 Select Control

#### System



Keypad



Timeclock



Mobile  
device



Pico®



Third-party  
integration

#### Standalone



**Pico®**  
for controlling a single  
shade or multiple shades  
with one button press.




**4-group RF**  
for assigning a group  
of shades to each of  
the four group buttons  
on the remote.

**Please note:** Product options may vary depending on application and intended use. For more technical information, reference [www.lutron.com](http://www.lutron.com) or work with your qualified Lutron provider. Product availability is subject to change.

## Step 4

## Window Measurements


Measure the window opening to the nearest 1/8 inch at points A through F, and enter the values below:



A \_\_\_\_\_ inches/mm

B \_\_\_\_\_ inches/mm

C \_\_\_\_\_ inches/mm



D \_\_\_\_\_ inches/mm

E \_\_\_\_\_ inches/mm

F \_\_\_\_\_ inches/mm

Smallest width: \_\_\_\_\_ inches/mm


Largest height: \_\_\_\_\_ inches/mm

## Step 5


## Shade Mount (choose one)

### Inside Mount


#### Without Fascia




Depth required  
for full recess:  
3.54 in (90 mm)



#### With Fascia




Depth required  
for full recess:  
4.50 in (114 mm)



### Outside Mount


#### On Trim



**Width:**  
Your shade can be  
as wide as you want,  
depending on what you  
want the fabric to cover.

Width: \_\_\_\_\_  
inches/mm

#### Above Trim



**Height:**  
Measure to the nearest  
1/8 inch from the top of the  
headrail mounting location\*  
to the window sill.

Height: \_\_\_\_\_  
inches/mm

**\*Note:** The top of the  
headrail must be at least  
5.25 in (133 mm) above  
the top edge of the  
window trim.

## Step 6

## Select Fabric

Utilize the insulating Honeycomb or Roller Essentials fabric binder or visit [www.lutron.com/fabrics](http://www.lutron.com/fabrics)

Fabric P/N: \_\_\_\_\_

For more information, please download  
The Lutron Fabric Collections mobile  
app at the Apple® store.

For more information, please visit [www.lutron.com](http://www.lutron.com) or call **1(800) 446-1503**

[www.lutron.com](http://www.lutron.com)



World Headquarters 1.610.282.3800

24/7 Technical Support 1.800.523.9466

Customer Service 1.888.LUTRON1 (1.888.588.7661)

