



Symbol	Model Number	Description	Qty
	RMJS-8T-DV-B	PowPak dimming module with 0–10V	4
	LRF2-DCRB-WH	Radio Powr Savr wireless daylight sensor	1
	LRF2-OKLB-P-WH	Radio Powr Savr wireless corner-mount occupancy sensor	1
	PJ2-3BRL-GWH-L01	Pico wireless 3-button with raise/lower control	2
	PICO-WBX-ADAPT	Pico wallbox adapter	2
	HJS-1-FM	Vive wireless Hub	Shared

Control Functionality

Occupant Enters:

All lights automatically turn on to 50% light level. Occupant turns on lights to maximum level manually. Maximum light level is set to 80%.

When Occupied:

Automatic: Overhead lights dim/brighten based on daylight availability. There are two perimeter daylight zones.
Manual: Occupant uses wall dimmers to set desired light levels for both general and white-board lights.

Occupant Exits:

All lights automatically turn off 15 minutes after all occupants exit.

System Events:

Demand Response: All lights automatically dim 20% during demand events.

Code Notes: For non-daylit classrooms, all general lighting can be connected to a single 0–10V dimming module.

Go to lutron.com/vive for complete compatibility and design details.

This solution requires 0–10V enabled ballasts and drivers by others.