

**Compatible Controls  
Hi-lume A-Series LED Driver**

3-Wire Controls							
Product	Part Number	Description	120V Dimmer Rating (A)	277V Dimmer Rating (A)	Fixtures per Dimmer		Measured Light Output Range (w/ A-Series Driver)
					120V	277V	
NovaT*	NTF-10-	single-pole, 120V, 16A	16		1 - 38	-	100% - 1%
	NTF-103P-	single-pole/3-way, preset, 120V, 8A	8		1 - 19	-	100% - 1%
	NTF-10-277-	single-pole, 277V, 8A		8	-	1 - 44	100% - 1%
	NTF-103P-277-	single-pole/3-way, preset, 277V, 6A		6	-	1 - 33	100% - 1%
Nova	NF-10-	single-pole, 120V, 16A	16		1 - 38	-	100% - 1%
	NF-103P-	single-pole/3-way, preset, 120V, 8A	8		1 - 19	-	100% - 1%
	NF-10-277-	single-pole, 277V, 8A		8	-	1 - 44	100% - 1%
	NF-103P-277-	single-pole/3-way, preset, 277V, 6A		6	-	1 - 33	100% - 1%
Vareo	VF-10-	single-pole/3-way, 120V, 8A	8		1 - 19	-	100% - 1%
Skylark	SF-10P-	single-pole, 120V, 8A	8		1 - 19	-	100% - 1%
	SF-103P-	single-pole/3-way, 120V, 8A		8	-	1 - 44	100% - 1%
	SF-12P-277-	single-pole, 277V, 6A		6	-	1 - 33	100% - 1%
	SF-12P-277-3	single-pole/3-way, 277V, 6A		6	-	1 - 33	100% - 1%
Diva	DVF-103P-	single-pole/3-way, 120V, 8A, gloss finish	8		1 - 19	-	100% - 1%
	DVSCF-103P-	single-pole/3-way, 120V, 8A, satin finish	8		1 - 19	-	100% - 1%
	DVF-103P-277-	single-pole/3-way, 277V, 6A, gloss finish		6	-	1 - 33	100% - 1%
	DVSCF-103P-277-	single-pole/3-way, 277V, 6A, satin finish		6	-	1 - 33	100% - 1%
Ariadni	AYF-103P-	single-pole/3-way, 120V, 8A	8		1 - 19	-	100% - 1%
	AYF-103P-277-	single-pole/3-way, 277V, 8A		8	-	1 - 44	100% - 1%
Vierti	VTF-6A-	single-pole/multi-location, 120/277V, 6A	6	6	1 - 14	1 - 33	100% - 1%
Maestro	MAF-6AM-	single-pole/multi-location, 120V, 20ballasts/6A, gloss finish	6		1 - 14	-	100% - 1%
	MAF-6AM-277-	single-pole/multi-location, 277V, 20ballasts/6A, gloss finish		6	-	1 - 33	100% - 1%
	MSCF-6AM-	single-pole/multi-location, 120V, 20ballasts/6A, satin finish	6		1 - 14	-	100% - 1%
	MSCF-6AM-277-	single-pole/multi-location, 277V, 20ballasts/6A, satin finish		6	-	1 - 33	100% - 1%
Maestro Wireless	MRF2-F6AN-DV-	single-pole/multi-loation, 120/277V, 20 ballast/6A	6	6	1 - 14	1 - 33	100% - 1%
RadioTouch	RTA-RX-F-	controller, 120/277V, 16A	16	16	1 - 38	1 - 88	100% - 1%
Spacer System	SPSF-6A-	single-pole, 120V, 6A	6		1 - 14	-	100% - 1%
	SPSF-6A-277-	single-pole, 277V, 6A		6	-	1 - 33	100% - 1%
	SPSF-6AM-	multi-location, 120V, 6A	6		1 - 14	-	100% - 1%
	SPSF-6AM-277-	multi-location, 277V, 6A		6	-	1 - 33	100% - 1%
Lyneo Lx	LXF-103PL-	single-pole/3-way, preset, 120V, 8A	8		1 - 19	-	100% - 1%
	LXF-103PL-277-	single-pole/3-way, preset, 277V, 6A		6	-	1 - 33	100% - 1%
Interfaces	PHPM-3F(-DV)	3-wire fluorescent interface	16	16	1 - 38	1 - 88	100% - 1%
RadioRA2	RRD-F6AN-DV-	single-pole/multi-location, 120/277V, 20 ballast/6A	6	6	1 - 14	1 - 33	100% - 1%
GRAFIK Eye QS	QSG- P120	control unit, 120/277V, 16A per power module			64 per EcoSystem link		100% - 1%
GRAFIK Eye	GRX-310	control unit, 120/277V, 16A per power module			64 per EcoSystem link		100% - 1%

**Compatible Controls  
Hi-lume A-Series LED Driver**

EcoSystem Controls					
Product	Part Number	Description	Fixtures per Dimmer		Measured Light Output Range (w/ A-Series Driver)
			120V	277V	
Energi Savr Node	QSN-2ECO-S	EcoSystem Energi Savr Node with 2 EcoSystem Digital Links	64 per EcoSystem link		100% - 1%
	QSN-1ECO-S	EcoSystem Energi Savr Node with 1 EcoSystem Digital Link	64 per EcoSystem link		100% - 1%
GRAFIK Eye QS	QSGRJ-6E-	6- zone GRAFIK Eye QS Main Unit with EcoSystem (Non-RF) 120-127 V or 220-240 V; 1 link	64 per EcoSystem link		100% - 1%
	QSGRJ-8E-	8- zone GRAFIK Eye QS Wireless with EcoSystem Main Unit 120-127 V or 220-240 V; 1 link	64 per EcoSystem link		100% - 1%
	QSGRJ-16E-	16- zone GRAFIK Eye QS Wireless with EcoSystem Main Unit, 120-127 V or 220-240 V; 1 link	64 per EcoSystem link		100% - 1%
EcoSystem Control Interfaces	CS-1L-WM	Standard Mount (shipped with no enclosure) 1 Link	64 per EcoSystem link		100% - 1%
	CS-2L-WM	Standard Mount (shipped with no enclosure) 2 Link	64 per EcoSystem link		100% - 1%
	CS-1L-CM	Contractor Mount (shipped with no enclosure) 1 Link	64 per EcoSystem link		100% - 1%
	CS-2L-CM	Contractor Mount (shipped with no enclosure) 2 Link	64 per EcoSystem link		100% - 1%