

# HomeWorks.slb

**2B**

HWI-2B-WH  
Two Button Keypad  
Location: X  
(1 Gang US Backbox by Others)

**2SE**

HWI-2SE-WH  
European Style  
Two Button Keypad  
Location: X  
(UK/German Backbox)

**4se-ir**

HWI-4SE-IR-WH  
European Style  
Four Button Keypad w/DH,  
Raise/Lower, and IR Receiver  
Location: X  
(UK/German Backbox)

**4SE-M**

HWI-4SE-M-WH  
European Style  
Four Button Keypad w/DH  
and Raise/Lower  
Location: X  
(UK/German Backbox)

**5S-IR**

HWI-5S-IR-WH  
Five Button Keypad  
with IR Receiver  
Location: X  
(1 Gang US Backbox by Others)

**5S-M**

HWI-5S-M-WH  
Five Button Keypad  
with Raise/Lower  
Location: X  
(1 Gang US Backbox by Others)

**5S-NM**

HWI-5S-NM-WH  
Five Button Keypad  
No Raise/Lower  
Location: X  
(1 Gang US Backbox by Others)

**8SE-IR**

HWI-8SE-IR-WH  
European Style  
Eight Button Keypad w/DH,  
Raise/Lower, and IR Receiver  
Location: X  
Dimensions:  
3.375"(H) x 3.375"(W) x 1"(D)

**8SE-M**

HWI-8SE-M-WH  
European Style  
Eight Button Keypad w/DH  
and Raise/Lower  
Location: X  
Dimensions:  
3.375"(H) x 3.375"(W) x 1"(D)

**CCI**

HWI-CCI-B  
Wired Contact Closure  
Input Interface  
Dimensions:  
8.5"(H) x 3"(W)

**CCO**

HWI-CCO-B  
Wired Contact Closure  
Output Interface  
Dimensions:  
8.5"(H) x 3"(W)

**ENC-CC**

HWI-ENC-CC  
10" Low-Voltage Enclosure  
Dimensions:  
10.25"(H) x 4.5"(W) x 3.88"(D)

**H4P5 PROCESSOR**

H4P5-XXX  
4 Series Processor #1  
Dimensions:  
13.34"(H) x 6.47"(W) x 1.38"(D)  
Mounted inside of a:  
HWI-424-120  
24" Low-Voltage Enclosure  
Dimensions:  
24"(H) x 15.13"(W) x 3.88"(D)

**H8P5 PROCESSOR**

H8P5-XXX  
8 Series Processor #1  
Dimensions:  
11.98"(H) x 11.98"(W) x 2.32"(D)

**HD-RD**

HD-RD-WH  
Maestro Remote  
Dimmer  
Location: X  
(1 Gang US Backbox by Others)

**HD-RS**

HD-RS-WH  
Maestro Remote  
Switch  
Location: X  
(1 Gang US Backbox by Others)

**HR-CCI-6-SW**

HR-CCI-6-SW  
HomeWorks RF  
Contact Closure  
Input Interface  
Dimensions:  
3.25"(H) x 3.58"(W) x 1.375"(D)

**HRP5-120**

HRP5-120  
HomeWorks RF  
Processor  
Dimensions:  
7"(H) x 11.5"(W) x 1.25"(D)

**HR-REP-120**

HR-REP-120  
Hybrid Repeater  
Dimensions:  
2.94"(H) x 4.69"(W) x 1.375"(D)

**HRT-3LD**

HRT-3LD  
HomeWorks RF  
Lamp Dimmer  
Dimensions:  
4.375"(H) x 2.375"(W) x 0.94"(D)

**HRT-6LRL**

HRT-6LRL-C-SW  
HomeWorks RF  
Six Button Tablet  
Control w/ Raise/Lower  
Dimensions:  
3.25"(H) x 3.56"(W) x 1"(D)

**HR-VCRX-SW**

HR-VCRX-SW  
HomeWorks RF  
Car Visor Receiver  
Dimensions:  
3.25"(H) x 3.56"(W)

**HR-VCTX-SW**

HR-VCTX-SW  
HomeWorks RF  
Car Visor Transmitter  
Dimensions:  
1.5"(H) x 3.19"(W) x 0.75"(D)

**HWBP-2S**

HWBP-2S  
Remote Power Panel  
With Breakers & HWI-MI  
Dimensions:  
24"(H) x 14.375"(W) x 3.88"(D)

**HWBP-8D**

HWBP-8D  
Remote Power Panel  
With Breakers & HWI-MI  
Dimensions:  
59"(H) x 14.375"(W) x 3.88"(D)

**HWD-6D**

HWD-6D-WH  
Maestro Dimmer  
Location: X  
(1 Gang US Backbox by Others)

**HWD-8ANS**

HWD-8ANS-WH  
Maestro Switch  
Location: X  
(1 Gang US Backbox by Others)

**HWV-1000NS**

HWV-1000NS-WH  
Varies Switch  
Location: X  
(1 Gang US Backbox by Others)

**HWI-CIR**

HWI-CIR-WH (CPN815)  
Ceiling Mounted Infrared Receiver  
Dimensions:  
7.5"(H) x 6.25"(W) x 5.25"(D)

**HWI-HHP-LD**

HWI-HHP-LD  
Handheld Lighting  
Programmer  
Dimensions:  
8.1"(H) x 13.3"(W) x 14.9"(D)

**HWI-LCC-2GR-CPN2627**

HWI-LCC-2GR-BL/BR-CPN2627  
Address: Area:  
Function: Lamp Card  
Zone Raise/Lower  
(2 Gang US Backbox by Others)

**HWI-MI**

HWI-MI-120  
Module Interface  
Dimensions:  
13.13"(H) x 3"(W) x 3.63"(D)

**HWI-PHAST**

HWI-PHAST  
HomeWorks to PHAST Interface  
DB9 to HWI RS232 Port &  
RJ-45 to PHAST Link Port  
Dimensions:  
4.1"(H) x 5.3"(W) x 5.5"(D)

**PPS1-120-15DC-3A**

PPS1-120-15DC-3A  
Enclosed-Mounted Power Supply  
Supports an additional 500 LEDs  
on a wired keypad link

**PPS2-120-15DC-3A**

PPS2-120-15DC-3A  
Enclosed-Mounted Power Supply  
Supports an additional 1000 LEDs  
on a wired keypad link

**HWI-Q96**

HWI-Q96  
50Aas Integrator  
for HomeWorks &  
Shiva OED  
Dimensions:  
4.56"(H) x 2"(W) x 1"(D)

**HWI-TEL9**

HWI-TEL9  
Telephone Interface  
Dimensions:  
12.5"(H) x 6.13"(W) x 3.31"(D)

**HWI-WLB**

HWI-WLB  
Wire Landing Board  
Dimensions:  
11"(H) x 1.375"(W)

**HWI-WPM**

HWI-WPM-6D-120  
6 Zone Wallbox  
Power Module  
(4 Gang US Backbox by Others)

**HWS-3B**

HWS-3B  
3 Button Signature  
Series Keypad  
Location: X  
\*Requires Lutron Backbox  
WBOX-54A-Q1

**HWS-4B**

HWS-4B  
4 Button Signature  
Series Keypad  
Location: X  
\*Requires Lutron Backbox  
WBOX-54A-Q1

**HWV-1000D**

HWV-1000D-WH  
Varies Dimmer  
Location: X  
(1 Gang US Backbox by Others)

**HWV-600D**

HWV-600D-WH  
Varies Dimmer  
Location: X  
(1 Gang US Backbox by Others)

**HWV-FDB**

HWV-FDB-8A-WH  
Lutron Tapscout Ballast  
Varies Dimmer  
Location: X  
(1 Gang US Backbox by Others)

**KP10**

HWI-KP10-WH  
Ten Button Keypad  
Location: X  
(1 Gang US Backbox by Others)

**KP15**

HWI-KP15-WH  
Fifteen Button Keypad  
Location: X  
(2 Gang US Backbox by Others)

**KP5**

HWI-KP5-WH  
Five Button Keypad  
Location: X  
(1 Gang US Backbox by Others)

**KP5-DN**

HWI-KP5-DN-WH  
5 Button Keypad  
with Raise/Lower  
Location: X  
\*Requires Lutron Backbox  
241399

**KP5-DW**

HWI-KP5-DW-WH  
5 Button Keypad  
with Raise/Lower  
Location: X  
\*Requires Lutron Backbox  
241399

**KPCC-LB**

HWI-KPCC-LB-WH  
8 Button Keypad  
with Large Button  
Contact Closure Keypad  
Location: X  
(1 Gang US Backbox by Others)

**KPCC-M**

HWI-KPCC-M-WH  
10 Slim Button &  
2 Large Button  
Contact Closure Keypad  
Location: X  
(1 Gang US Backbox by Others)

**KPCC-NM**

HWI-KPCC-NM-WH  
14 Button Contact  
Closure Keypad  
Location: X  
(1 Gang US Backbox by Others)

**LB5-DC1**

HWI-LB5-DC1-WH  
Five Button Keypad  
with Raise/Lower  
Location: X  
\*Requires Lutron Wallbox  
241633

**LB6**

HWI-LB6-WH  
Six Button Keypad  
Location: X  
(1 Gang US Backbox by Others)

**LB9**

HWI-LB9-WH  
Nine Button Keypad  
Location: X  
(2 Gang US Backbox by Others)

**LV17-120**

HWI-LV17-120  
17" Low-Voltage Enclosure  
Dimensions:  
17.25"(H) x 9.25"(W) x 3.88"(D)

**LV24-120**

HWI-LV24-120  
24" Low-Voltage Enclosure  
Dimensions:  
24"(H) x 15.13"(W) x 3.88"(D)

**LV32-120**

HWI-LV32-120  
32" Low-Voltage Enclosure  
Dimensions:  
32"(H) x 14.375"(W) x 3.88"(D)

**PNL-5**

HWI-PNL-5  
Remote Power  
Feed-Through Panel  
with Module Interface  
Location: X  
Dimensions:  
32"(H) x 14.375"(W) x 3.875"(D)

**PNL-8**

HWI-PNL-8  
Remote Power  
Feed-Through Panel  
with Module Interface  
Location: X  
Dimensions:  
59"(H) x 14.375"(W) x 3.88"(D)

**PNL-8 with 8 Series Processor**

**LV32 with 8 Series\_2WLBs\_1CCO\_1CCI**

**LV32 with 8 Series\_2WLBs\_2CCOs**

- WIRE TYPE KEY**
- ▲ TYPE A: Two pair [one pair #18 AWG (1.0mmSO), one pair #18-22 AWG (1.0-0.5mmSO) twisted shielded] Class 2 wire, Lutron wire model # GRX-3465-500 Non-Platinum
  - ▲ TYPE B: Standard RS-232 Cable (all pins straight through).
  - ▲ TYPE C: One pair #18-22 AWG (1.0-0.5mmSO) twisted shielded Class 2 wire.
- REFER TO THE HOMEWORKS TECHNICAL REFERENCE GUIDE FOR WIRING OF YOUR HOMEWORKS SYSTEM.
- DO NOT EXCEED 32 WALLSTATION ADDRESS PER KEYPAD LINK.
  - WALLSTATION KEYPAD WIRING CAN BE DAISSY CHAINED (LOOP).
  - 1-TAPPED OR HOME-RUN
  - PANEL LINK WIRING MUST BE DAISSY CHAINED (LOOP) ONLY.
  - DO NOT DISSIPATE GAIN (LOOP) MORE THAN 10 WALLSTATION TOGETHER

**WIRETYPE KEY**

- HWI-PNL-8  
Remote Power  
Feed-Through Panel  
with Module Interface  
Location: X  
Dimensions:  
59"(H) x 14.375"(W) x 3.88"(D)
- HWI-PNL-5  
Remote Power  
Feed-Through Panel  
with Module Interface  
Location: X  
Dimensions:  
32"(H) x 14.375"(W) x 3.875"(D)
- HWI-LV32-120  
32" Low-Voltage Enclosure  
with (1) 8-Series Processor  
(2) HWI-WLB & (1) HWI-CCO-B  
Dimensions:  
32"(H) x 14.375"(W) x 3.88"(D)