

Ivalo® Finiré™ LED Recessed Lighting



LED Recessed Lighting

Why Finiré™?

Finiré eliminates guesswork by ensuring 100% compatibility between LED fixtures, drivers, and controls. It is available in 15W and 22W; the 15W fixture provides high energy efficiency while the 22W fixture provides high performance. Both deliver smooth, flicker-free dimming.

This complete solution combines an architectural-grade fixture with a high-performance Hi-lume® LED driver designed to work with Lutron RadioRA® 2, HomeWorks® QS, and GRAFIK Eye® QS control systems, and compatible Lutron dimmers/controls.

Offer Your Customers:

High-quality light output

Proprietary low-glare blended lensing system provides the pleasing appearance of an incandescent while surpassing the energy efficiency of compact fluorescents. (No multiple shadows, striations, or visible LEDs)

Immediate light output

No warm-up time.

High performance

Smooth, flicker-free dimming from 100% down to 1% utilizing Lutron Hi-lume® drivers.

Color temperature options

Equivalent to the light output of 60–75 Watt incandescent lighting. (see page 6)

Environmentally friendly fixtures

All fixtures are RoHS compliant.

Reliability

3 year warranty. See www.ivalolighting.com for full warranty details.

Manufactured in the USA

Why Provide LED Fixtures?

Ensuring compatibility between an LED dimmer, driver, and fixture can be difficult.

Finiré LED recessed lights simplify the specification process by offering a complete energy-saving solution.

Finiré provides both LED light and light control in one source. And having an all-in-one product will help you sell more on every job, grow revenue, and expand your business.

Finiré offers many additional benefits, including:

Energy compliance

Integrated OSRAM LED module that meets ENERGY STAR and California Title 24 standards on all 15W models. (see page 6)

Extended LED lamp and driver life

Finiré contains a high-performance heat-sink for maximum LED life and the Lutron Hi-lume LED driver—both rated for 50,000 hours.

Versatile design

Downlight, wall wash, and adjustable fixture options with trimmed or trimless assemblies are available.

Straightforward installation

Choose from rigid hanging or adjustable hanging bars, with aim and lock options. (See page 4)

Project versatility

Non-insulation contact (Non-IC) and Insulation Contact (IC) housing options are available. The IC housings are available for the 15W line only, airtight and Chicago Plenum rated.

Guaranteed compatibility*

The fixtures were designed for ideal compatibility and performance with Lutron drivers and Lutron controls. Finiré has been tested to work well with most Lutron products including Nova®, Vareo®, Skylark®, Maestro®, Vierti®, and Ariadni®.

Easy maintenance

Field-replaceable LED light module and driver. You can change the color temperature and wattage after Finiré is installed without removing the fixture housing from the ceiling.


Specification

Standard housing dimensions*

Length: 12.7"

Width: 9.5"

Height: 6.4"



*Reference the Finiré™ specification sheets for drawings and dimensions by fixture type at www.ivaloighting.com.

Fixture Types and Options

	Residential	Commercial
Type	Downlight [†] , Wall Wash, Adjustable	Downlight [†] , Wall Wash, Adjustable
Size (opening)	4" [†]	4" [†]
Housing	Non-IC, IC	Non-IC
Aperture Style	Round [†] , Square	Round [†] , Square
LED Wattage	15W [†] (Non-IC or IC), 22W (Non-IC only)	22W [†]
Color Temperature	2700K [†] , 3100K, 3500K	3500K [†] , 4100K
Beam	Wide [†] , Medium, Pinhole, Slotted Pinhole	Wide [†] , Medium, Pinhole, Slotted Pinhole
Trim	Round [†] , Round Trimless, Square, Square Trimless	Round [†] , Round Trimless, Square, Square Trimless
Hanging	14–24" Adjustable Hanging Bars [†] , 8–13" Adjustable Hanging Bars, C-Channel	14–24" Adjustable Hanging Bars [†] , 8–13" Adjustable Hanging Bars, C-Channel
Control Method	Forward Phase 2-wire to 1% [†]	EcoSystem® (3-wire) to 1% [†] , Lutron 3-wire to 1%
Ceiling Thickness	Up to 0.5" [†] , 1", 1.5", 2" Plaster Rings	Up to 0.5" [†] , 1", 1.5", 2" Plaster Rings

[†] standard option
[‡] neutral wire required

Product Features

All Fixtures

Adjustable hanging bars 8–24"
(Rigid hanging options also available)


Adjustable mounting brackets

Ceiling

Mesh mud ring for clean plastering
(Trimless versions only)

Clips (x2) to hold trim


Removable trim assemblies
(Designed for field-replaceable
LED light module and driver)



Adjustable Fixtures

Tilt adjustability up to 42°
(Accommodates sloped ceilings)


Rotational adjustability up to 357°



Options

Trim Finish and Color Options


	Matte White*	Matte Black	Soft Glow	Clear Bright Alzak	Wheat Alzak	Oil-Rubbed Bronze
Round*	•	•	•	•	•	•
Round Trimless	•	•	•	•	•	•
Round Pinhole	•					
Round Slotted Pinhole	•					
Square	•	•	•			
Square Trimless	•	•				
Square Pinhole	•					




Round*




Round Trimless



Round Pinhole



Round Slotted Pinhole



Square



Square Trimless




Square Pinhole

Lens Options


	Micro Prism Solite™	Frosted Glass	None	
Round	•	•	•	
Square	•	•	•	

Decorative Trim Options


	Clear Glass	Frosted Glass Ring	Tier Center Frosted Glass	Stainless Steel Bezel
Round	•	•	•	•
Square	•	•		



Round Clear Glass




Round Frosted Glass Ring




Round Tier Center Frosted Glass



Round Stainless Steel Bezel



Square Clear Glass



Square Frosted Glass Ring


Performance

Light Output Comparison

	Ivalo Finiré™ LED								Incandescent*	
Color Temperature (Kelvin)	4100°K	3500°K	3100°K	2700°K	4100°K	3500°K	3100°K	2700°K	2700°K	
Lumens (see note)	900	840	770	700	1180	1050	960	880	850	1200
Wattage	15W				22W				60W	75W

Note: The chart above represents standard fixture and lamp performance for comparisons only. Reference Finiré specification sheets for photometric data and efficiency losses by trim type.

Energy-Efficient Lighting Comparison



How to Specify

F D T 4 R N 15 27 WD F1 B2 XX - R4466 MW SO WL
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16

Fixture Options

- 1 Family**
F = Finiré™ Recessed Lights
-
- 2 Type**
D = Downlight (standard)
W = Wall Wash
A = Adjustable
-
- 3 Flange**
T = Trimmed (standard)
Z = Trimless
-
- 4 Size**
4 = 4" Series
-
- 5 Aperture**
R = Round (standard)
S = Square
-
- 6 Housing**
N = Non-insulation Contact
I = Insulation Contact
-
- 7 LED Wattage**
15 = 15W
22 = 22W
-
- 8 Color Temperature**
27 = 2700K
31 = 3100K
35 = 3500K
41 = 4100K
-
- 9 Beam**
WD = Wide Beam Spread (standard)
MD = Medium Beam Spread
PH = Pinhole
SL = Slotted Pinhole
-
- 10 Control Method**
31 = 3-wire, 120V~ LED Driver
37 = 3-wire, 277V~ LED Driver
E1 = EcoSystem®, 120V~ Driver
E7 = EcoSystem, 277V~ Driver
F1 = Forward Phase, 120V~ Driver
-
- 11 Hanging**
B2 = 14–24" Adjustable Hanging Bars (standard)
B6 = 8–13" Adjustable Hanging Bars
C4 = C-Channel
-
- 12 Ceiling Thickness**
XX = Up to 0.5"
10 = 1.0" Plaster Ring
15 = 1.5" Plaster Ring
20 = 2.0" Plaster Ring

Trim Options

- 13 Trim**
R4466 = Round Downlight (standard)
R4966 = Round Wall Wash
R4500 = Round Adjustable
R4105 = Round Pinhole Downlight
R4106 = Round Slotted Adjustable
R0404 = Square Downlight
R0104 = Square Wall Wash
R0204 = Square Adjustable
R4004 = Square Pinhole Downlight
Z4466 = Trimless Round Downlight
Z4966 = Trimless Round Wall Wash
Z4500 = Trimless Round Adjustable
Z0404 = Trimless Square Downlight
Z0104 = Trimless Square Wall Wash
Z0204 = Trimless Square Adjustable
-
- 14 Finish**
MW = Matte White (standard)
CL = Clear Bright Alzak
BL = Matte Black
SG = Soft Glow
WE = Wheat Alzak
RB = Oil-rubbed Bronze
-
- 15 Lens**
SO = Micro Prism Solite™
FG = Frosted Glass
XX = None
-
- 16 Options**
XX = None (standard)
WL = Wet Location
TF = Round Tier Center Frosted Glass*
SS = Round Stainless Steel Bezel*
FR = Round Frosted Glass Ring*
CR = Round Clear Glass*
FQ = Square Frosted Glass Ring*
CQ = Square Clear Glass*



www.ivalolighting.com

Lutron Electronics Co., Inc.
7136 Suter Road
Coopersburg, PA 18036-1299

For customer service or quotes call
610.282.7472 or email ivalo@lutron.com

© 01/2013 Lutron Electronics Co., Inc.
Printed in the U.S.A.
P/N 367-2166 REV H

