

OMX Wallstations.slb

EOMX-2B
Address: X
Function: Scenes 1 & Off
Requires Lutron Wallbox
P/N 241-683

EOMX-4S
Address: X
Function: Scenes 1-4 & Off
with Zone Roller/Lower
P/N 241-685

EOMX-4S-IR
Address: X
Function: Scenes 1-4 & Off
with Zone Roller/Lower
and Infrared Receiver
Requires Lutron Wallbox
P/N 241-683

EOMX-8S
Address: X
Function: Scenes 1-8 & Off
with Zone Roller/Lower
Requires Lutron Wallbox
P/N 241-685

EOMX-8S-IR
Address: X
Function: Scenes 1-8 & Off
with Zone Roller/Lower
and Infrared Receiver
Requires Lutron Wallbox
P/N 241-685

FOMX-1B-SL
Address: X
Function: Toggle on/off
(1 Gang US Backbox by Others)

GR6-HHP
Handheld Lighting
Programmer
Dimensions:
7.31"(H) x 4.61"(W) x 0.13"(D)

GRX-8IT
Infrared Transmitter
Function: Scenes 1-8 and Off
with Zone Roller/Lower
Dimensions:
5.6875"(H) x 1.5"(W) x 0.875"(D)

GRX-IT
Infrared Transmitter
Function: Scenes 1-4 and Off
with Zone Roller/Lower
Dimensions:
5.6875"(H) x 1.5"(W) x 0.875"(D)

MX-RPTR
120 Volt 10A Center Feed
Data Repeater
Dimensions:
7.75"(H) x 5"(W) x 2.5"(D)
Wallbox area and cover area 10" maximum size. Weigh 8.2000lb.
We advise you use a 10" x 10" x 1" panel to support this.
A maximum of 10 120V/10A units may be used per line.
Maximum line length is 1000 feet.
INDICATING LOCATION TO BE DETERMINED BY THE INSTALLER.

NT-6B-EXT-E-CPN1537

NTOMX-2B
Address: X
Function: Scenes 1 and Off
(1 Gang US Backbox by Others)

NTOMX-4B
Address: X
Function: Scenes 1-4 and Off
(1 Gang US Backbox by Others)

NTOMX-4S
Address: X
Function: Scenes 1-4 & Off
with Zone Roller/Lower
(1 Gang US Backbox by Others)

NTOMX-4S-IR
Address: X
Function: Scenes 1-4 & Off
with Infrared Receiver
(1 Gang US Backbox by Others)

NTOMX-4S-NRL
Address: X
Function: Scenes 1-4 & Off
(1 Gang US Backbox by Others)

NTOMX-62J
Address: X, X, X
Function: Manual Side Adjust
(1 Gang US Backbox by Others)

NTOMX-HHPJ
Address: X
Function: Scenes 1-4 & Off
with Infrared Receiver
(1 Gang US Backbox by Others)

NTOMX-KP10
Address: X
Function: Scenes 1-10 & Off
with Full-On Function
(1 Gang US Backbox by Others)

NTOMX-KP15
Address: X
Function: Scenes 1-15 & Off
with Full-On Function
(2 Gang US Backbox by Others)

NTOMX-KP5
Address: X
Function: Scenes 1-5 & Off
with Full-On Function
(1 Gang US Backbox by Others)

NTOMX-KS
Address: X
Function: Scenes 1 & Off
(1 Gang US Backbox by Others)

NTOMX-KS/4S-BYA
Address: X
Function: Scenes 1-4 and Off
with Zone Roller/Lower
and Infrared Receiver
Requires Lutron Wallbox
P/N 241-683

NTOMX-KS-4S-E-CPN1144
Address: X
Function: Scenes 1-4 & Off
with Zone Roller/Lower
KEYSWITCH: Enable/Disable 4S portion
(4 Gang US Backbox by Others)

NTOMX-KS-CPN0733
Address: X
Function: Scenes 1 & Off
(1 Gang US Backbox by Others)

NTOMX-LB6
Address: X
Function: Scenes 1-6 & Off
(1 Gang US Backbox by Others)

NTOMX-LB6-RL
Address: X
Function: Scenes 1-6 & Off
(1 Gang US Backbox by Others)

NTOMX-LB9
Address: X
Function: Scenes 1-9 & Off
(2 Gang US Backbox by Others)

NTOMX-LB9-RL
Address: X
Function: Scenes 1-9 & Off
(2 Gang US Backbox by Others)

NT-RCP8-MX-CPN1031
Address: X
Function: Control
Connection Receptacle
(1 Gang US Backbox by Others)

OMX-2B-DW
Address: X
Function: Scenes 1-4 & Off
Requires Lutron Wallbox
P/N 241-229 Wallbox

OMX-3602-T
Address: X
Function: Scenes 1-4 and Off
(2 Gang US Backbox by Others)

OMX-3603-T
Address: X
Function: Scenes 1-4 and Off
(2 Gang US Backbox by Others)

OMX-3604-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-3606-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-3608-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-4602-T
Address: X
Function: Scenes 1-4 and Off
(2 Gang US Backbox by Others)

OMX-4603-T
Address: X
Function: Scenes 1-4 and Off
(3 Gang US Backbox by Others)

OMX-4604-T
Address: X
Function: Scenes 1-4 and Off
(3 Gang US Backbox by Others)

OMX-4606-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-4608-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-4616-T
Address: X, X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-4624-T
Address: X
Function: Scenes 1-4 and Off
(4 Gang US Backbox by Others)

OMX-4SLB-XW
Address: X
Function: Scenes 1-4 & Off
with Master Roller/Lower
Requires (1) Lutron backbox
P/N 241-663

OMX-4SLB-XWLG
Address: X
Function: Scenes 1-4 & Off
with master Roller/Lower
Requires (1) Lutron backbox
P/N 241-663

OMX-5C-DN
Address: X
Function: Scenes 1-4 and Off
Lutron does not recommend using
8 backbox with this installation.
Contact the factory for installation
instructions.

OMX-5C-DW
Address: X
Function: Scenes 1-4 and Off
Requires Lutron supplied
241399 Wallbox

OMX-7B-DW
Address: X
Function: Scenes 1-4 and Off
with Zone Roller/Lower
Requires Lutron
P/N 241-399 Wallbox

OMX-AV
Address: X
Function: Scenes 1-4 and Off
with Zone Roller/Lower
Requires Lutron
P/N 241-399 Wallbox

OMX-CC0-8
Address: X
Function: Infrared Receiver
Zones: X
Dimensions:
10.75"(H) x 5.75"(W) x 2"(D)

OMX-CI-NWK-E
Address: X
Function: Ethernet TCP/IP
Communication Interface
Dimensions:
5.26"(H) x 4.26"(W) x 1.06"(D)

OMX-CIR
Address: X
Function: Infrared Receiver
Zones: X
Dimensions:
3.75"(H) x 5.2"(W) x 2.5"(D)

OMX-CI-RS232
Address: X
Function: RS232 Control Interface
Dimensions:
5.26"(H) x 4.26"(W) x 1.06"(D)

OMX-DACPI & MW-PS
Address: X
Function: Automatic Daylight Control
Automatic
Function: Scenes 1-4
(4 Gang US Backbox by Others)

OMX-IO & IRPS
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-026

OMX-IO
Address: X
Function: Contact-Closure Interface
Dimensions:
5.26"(H) x 4.26"(W) x 1.06"(D)
Input 1:
Input 2:
Input 3:
Input 4:
Input 5:

OMX-LCC-2GR-CPN2626
Address: X
Function: Lamp Cord
Zone Roller/Lower
XXX-LCC-2GR-WH/BB-CPN2627-HBB
2 NT-6S-NFL-WH faceplates
P/N 241-663

OMX-LCC-SPLIT
Address: X
Function: Lamp Cord
Zone Roller/Lower
XXX-LCC-2GR-WH/BB-CPN2627-HBB
2 NT-6S-NFL-WH faceplates
P/N 241-663

OMX-RACP-CPN1123
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-027

OMX-RS232
Address: X
Function: RS232 Interface
Dimensions:
5.26"(H) x 4.26"(W) x 1.06"(D)

OMXSL-10-SQ-6G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-113

OMXSL-11-SQ-6G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-113

OMXSL-1-SQ-1G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-024

OMXSL-12-SQ-7G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-113

OMXSL-1-4SNRL-SQ-2G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-025

OMXSL-2-SQ-2G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-025

OMXSL-2-4SNRL-SQ-3G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-026

OMXSL-3-SQ-2G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-025

OMXSL-3-4SNRL-SQ-3G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-026

OMXSL-4-SQ-3G
Address: X
Function: Manual Side Adjust
Requires P/N 241-026 Backbox

OMXSL-4-4SNRL-SQ-4G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-027

OMXSL-5-SQ-3G
Address: X
Function: Manual Side Adjust
Requires Backbox P/N 241-026

OMXSL-5-4SNRL-SQ-4G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-027

OMXSL-6-SQ-4G
Address: X
Function: Manual Side Adjust
Requires P/N 241-027 Backbox

OMXSL-6-4SNRL-SQ-5G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-114

OMXSL-7-SQ-4G
Address: X
Function: Manual Side Adjust
Requires P/N 241-027 Backbox

OMXSL-7-4SNRL-SQ-5G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-114

OMXSL-8-4SNRL-SQ-6G
Address: X, X
Function: Manual Side Adjust
with (4) scene plus off selection station
Requires Backbox P/N 241-113

OMXSL-8-SQ-5G
Address: X
Function: Manual Side Adjust
Requires P/N 241-114 Backbox

OMXSL-9-SQ-5G
Address: X
Function: Manual Side Adjust
Requires P/N 241-114 Backbox

OMXSL-9-SQ-5G
Address: X
Function: Manual Side Adjust
Requires P/N 241-114 Backbox

OMXSL-8-SQ-5G
Address: X
Function: Manual Side Adjust
Requires P/N 241-114 Backbox

OMX-WCI
Address: X
Function: Manual Side Adjust
Input Interface
Dimensions:
2.3125" Dia.

SO-1BI
Address: X
Function: Toggle Scene
(1 Gang US Backbox by Others)

SO-1BN
Address: X
Function: Toggle Scene
(1 Gang US Backbox by Others)

SO-2BI
Address: X
Function: Toggle Scene
(1 Gang US Backbox by Others)

SO-2BN
Address: X
Function: Toggle Scene
(1 Gang US Backbox by Others)

SO-3BI
Address: X
Function: Toggle Scene 1 thru 3
(1 Gang US Backbox by Others)

SO-3BN
Address: X
Function: Toggle Scene 1 thru 3
(1 Gang US Backbox by Others)

SO-4BI
Address: X
Function: Toggle Scene 1 thru 4
(1 Gang US Backbox by Others)

SO-4BN
Address: X
Function: Toggle Scene 1 thru 4
(1 Gang US Backbox by Others)

SO-4NRLI
Address: X
Function: Toggle Scene 1-4 & Off
(1 Gang US Backbox by Others)

SO-4NRLN
Address: X
Function: Toggle Scene 1-4 & Off
(1 Gang US Backbox by Others)

SO-4SI
Address: X
Function: Toggle Scene 1-4 & Off
with Master Roller/Lower
(1 Gang US Backbox by Others)

SO-4SIRI
Address: X
Function: Scenes 1-4 & Off
with Roller/Lower & IR Receiver
(1 Gang US Backbox by Others)

SO-4SIRN
Address: X
Function: Scenes 1-4 & Off
with Roller/Lower & IR Receiver
(1 Gang US Backbox by Others)

SO-4SN
Address: X
Function: Scenes 1-4 & Off
with Roller/Lower & IR Receiver
(1 Gang US Backbox by Others)

SO-5BI
Address: X
Function: Scenes 1 thru 5
(1 Gang US Backbox by Others)

SO-5BN
Address: X
Function: Scenes 1 thru 5
(1 Gang US Backbox by Others)

SO-6BI
Address: X
Function: Scenes 1 thru 6
(1 Gang US Backbox by Others)

SO-6BN
Address: X
Function: Scenes 1 thru 6
(1 Gang US Backbox by Others)

SO-7BI
Address: X
Function: Scenes 1 thru 7
(1 Gang US Backbox by Others)

SO-7BN
Address: X
Function: Scenes 1 thru 7
(1 Gang US Backbox by Others)

SO-KS-4SN-CPN2685
Address: X
Function: Scenes 1-4 & Off
with Zone Roller/Lower
and Infrared Receiver
Requires Lutron Wallbox
P/N 241-683

WIRING NOTE
Lutron uses GRX-CBL-461 (5 Conductor Non-Plenum) or SO-CBL-461 (5 Conductor Plenum-rated). Others use 2 #14AWG (2.5mm²), 1 #6AWG #1461, and between points and 1 #16AWG (2.0mm²) for emergency wiring.