



**PHIFER**  
INCORPORATED

10 October 08

Re: Flame Retardance of Phifer SheerWeave Style 1000, SheerWeave 2000, SheerWeave 2100, SheerWeave 2360, SheerWeave 2390 and SheerWeave 2410, SheerWeave Plus 5%, 10% and 15%, SheerWeave/Fiberglass Twill Weave 1% and 3%

**PHIFER INCORPORATED** certifies that the following material furnished by our firm:

Phifer SheerWeave Fiberglass Vinyl Coated Fabric, All colors are in compliance with the following standard(s):

1. Flammability per California Administrative Code, Title 19, Public Safety, Subchapter 8, Article 4, Sections 1272 (C) and referenced Article 4, Section 1237, Paragraph (b), Small Scale test, Registration numbers FA-44203 and FA-44207.
2. NFPA 701-2004 TM #1, Standard Methods of Fire Test for Flame Resistant Textiles and Films 2004 Edition – Test Method #1 (small scale).
3. National Fire Protection Association, NFPA No. 101, "Life Safety Code", Class "A" rating. FLAME SPREAD INDEX = 20 SMOKE DEVELOPED VALUE = 145
4. Uniform Building Code, 1979 Edition, Part VIII, "Fire Resistive Standard for Fire Protection", Chapter 42 – Interior Wall and Ceiling Finish, Sections 4201-4205, Class I.
5. British Standard 5867: Part 2: 1980 (1993) Type B Performance Requirements.
6. NFPA 701-2004 TM#2, Flame Resistant Textiles and Films, 2004 Edition, Test 2, Large Scale – Single Flat Specimen.

If you have any questions or need further information, please contact me at 1-800-633-5955, ext 4754.

Sincerely,  
**PHIFER INCORPORATED**

Johnny Skinner  
Quality Control Manager