

**Manufacturer:** AURORA LIGHTING  
**Model Number Tested:** AU-DGU10L7/30  
**Other Model Numbers:** None

**Manufacturer's Description**

Type of device: LED Luna 7W PAR16 GU10  
 Operating voltage: 240V  
 Input Power: 7.0 W  
 Input Current: Not Specified  
 Input Frequency: 50Hz/60Hz

Control Type: Forward and Reverse Phase Control  
 Dimming Range: Not Specified  
 Output Power: Not Specified  
 Lumen Output: 435

**Lutron Test Results**

Date Tested: 17-Oct-13  
 Test Voltage: 240 V  
 Test Notes: Performance evaluated at 240V, 50Hz only.

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not recommended, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
<i>No applicable results</i>							
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4U-230-CE	1	31	9%	98%	29%	Start time in excess of 1 second at low end. Rating is per channel; total per module is 31.
Grafik QS	Grafik Eye QS Main Unit Family, 240V	1	5	10%	100%	31%	Rating is per output; total quantity per Main Unit is 15/20/23 for 3/4/6-Zone units, respectively.
Grafik Eye	GRX-3104-CE	1	8	9%	97%	29%	Rating is per output; total quantity per Main Unit is 16/23/23/23 for 2/3/4/6-Zone units, respectively.
ESN Phase Adaptive	LQSE-4A-D (L)*/QSNE-4A-D (L)*	1	14	9%	100%	30%	Start time in excess of 1 second at low end. Set load type to FP. Rating is for Zone 1. Rating for Zone 2-4 is 14.
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4U-230-CE	1	31	9%	98%	29%	Start time in excess of 1 second at low end. Rating is per channel; total per module is 31.
ESN Phase Adaptive	LQSE-4A-D (L)*/QSNE-4A-D (L)*	1	14	9%	100%	30%	Start time in excess of 1 second at low end. Set load type to FP. Rating is for Zone 1. Rating for Zone 2-4 is 14.
<i>Interfaces<sup>(3)</sup></i>							
	NGRX-ELVI-CE	1	17	8%	97%	29%	Start time in excess of 1 second at low end.
	NGRX-PB-CE	1	10	10%	98%	31%	Start time in excess of 1 second at low end.
Notes:	* Identical model numbers with different compatibility codes may have different performance; (L) means there is no compatibility code assigned; contact technical support for additional information (1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 21 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or [leds@lutron.com](mailto:leds@lutron.com).  
This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at [www.lutron.com/LEDtool](http://www.lutron.com/LEDtool).*