



# LUTRON® Product Report Card

ID 1075

**Manufacturer:** Bulbrite Industries, Inc.  
**Model Number Tested:** LED12A19/O/27K/D  
**Other Model Numbers:** LED12A19/O/30K/D, LED12A19GU24/27K/D, LED12A19GU24/30K/D

**Manufacturer's Description**

Type of device:	<u>LED A19 12W</u>	Control Type:	<u>Forward and Reverse Phase Control</u>
Operating voltage:	<u>120V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>12.0 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.15 A</u>	Lumen Output:	<u>Not Specified</u>
Input Frequency:	<u>60Hz</u>		

**Lutron Test Results**

Date Tested: 9-Aug-13  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not recommended, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Diva/ Skylark/ Skylark Contour/ Ariadni/ Toggler	C-L wall-mount dimmers (T1)*	1	12	12%	100%	34%	Low end trim required.
Maestro	MACL-153M (L)*	1	12	9%	100%	30%	Low end trim required.
Maestro Sensor	MSCL-OP153M (T2)*/ MSCL-VP153M (T2)*	1	12	19%	100%	44%	Low end trim required.
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	17	14%	100%	37%	High end and low end trim required.
Panel Module	HW/LP-RPM-4A-120	1	34	16%	100%	40%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 54.
Panel Module	HW/LP-RPM-4U-120	1	55	9%	100%	30%	High end and low end trim required. Rating is per channel; total per module is 55.
Grafik QS	Grafik Eye QS Main Unit Family	1	23	10%	100%	32%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 57.
Panel Module	GP (Harrier) Card	1	55	10%	100%	32%	High end and low end trim required. Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	23	10%	100%	32%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 34, 57, and 57 for 2, 4, and 6 zone units, respectively.
<i>Residential Systems</i>							
HomeWorks	HxD-6ND	1	17	14%	100%	37%	High end and low end trim required.
Panel Module	HW/LP-RPM-4A-120	1	34	16%	100%	40%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 54.

Panel Module	HW/LP-RPM-4U-120	1	55	9%	100%	30%	High end and low end trim required. Rating is per channel; total per module is 55.
Grafik QS	Grafik Eye QS Main Unit Family	1	23	10%	100%	32%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 57.
Panel Module	GP (Harrier) Card	1	55	10%	100%	32%	High end and low end trim required. Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	23	10%	100%	32%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 34, 57, and 57 for 2, 4, and 6 zone units, respectively.
<b>Interfaces<sup>(3)</sup></b>							
	PHPM-PA with Grafik Eye QS Main Unit	1	55	13%	100%	36%	High end and low end trim required.
	PHPM-WBX with 3-wire fluorescent control	1	55	13%	100%	36%	High end and low end trim required.
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; ( ) means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 12 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Low end trim required.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*