



LUTRON® Product Report Card

ID 1108

Manufacturer: Cree
Model Number Tested: BBR30-06527FLF-12DE26-1Uxxx
Other Model Numbers: BBR30-06527FLF-12DE26-1U_00

Manufacturer's Description

Type of device: LED BR30 9.5W d/c 2513
 Operating voltage: 120V
 Input Power: 9.5 W
 Input Current: 0.10 A
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumen Output: 650

Lutron Test Results

Date Tested: 3-Sep-13
 Test Voltage: 120 V
 Test Notes: None

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Diva/ Skylark/ Skylark Contour/ Ariadni/ Toggler	C-L wall-mount dimmers (T1)*	1	15	15%	92%	38%	Slight shimmer at low end.
Maestro	MACL-153M (L)*	1	15	12%	87%	35%	Low end trim required. Slight shimmer at low end.
Maestro Sensor	MSCL-OP153M (T2)*/ MSCL-VP153M (T2)*	1	15	15%	89%	38%	Low end trim required. Slight shimmer at low end.
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	12	5%	90%	23%	
Panel Module	HW/LP-RPM-4A-120	1	47	7%	93%	26%	Set load type to RP. Rating is per channel; total per module is 75.
Panel Module	HW/LP-RPM-4U-120	1	38	3%	100%	18%	Rating is per channel; total per module is 38.
Grafik QS	Grafik Eye QS Main Unit Family	1	16	6%	99%	25%	Rating is per output; total quantity per Main Unit is 40.
Panel Module	GP (Harrier) Card	1	38	9%	99%	30%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	16	6%	99%	25%	Rating is per output; total quantity per Main Unit is 24, 40, and 40 for 2, 4, and 6 zone units, respectively.
<i>Residential Systems</i>							
RadioRA 2	RRD-10ND	1	15	9%	93%	31%	
HomeWorks QS	HQRD-10ND	1	15	9%	93%	31%	
HomeWorks	HxD-6ND	1	12	5%	90%	23%	
Panel Module	HW/LP-RPM-4A-120	1	47	7%	93%	26%	Set load type to RP. Rating is per channel; total per module is 75.
Panel Module	HW/LP-RPM-4U-120	1	38	3%	100%	18%	Rating is per channel; total per module is 38.
Grafik QS	Grafik Eye QS Main Unit Family	1	16	6%	99%	25%	Rating is per output; total quantity per Main Unit is 40.
Panel Module	GP (Harrier) Card	1	38	9%	99%	30%	Rating is per output.

Grafik Eye 3000	Grafik Eye 3000 Family	1	16	6%	99%	25%	Rating is per output; total quantity per Main Unit is 24, 40, and 40 for 2, 4, and 6 zone units, respectively.
<i>Interfaces</i> ⁽³⁾							
	PHPM-PA with Grafik Eye QS Main Unit	1	75	8%	95%	28%	
	PHPM-WBX with 3-wire fluorescent control	1	75	8%	95%	28%	
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 15 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.