

**Manufacturer:** GE  
**Model Number Tested:** 67923 LED12DP30R930/25

67926 LED12DP30R927/25, 67922 LED12DP30R930/15, 67924 LED12DP30R930/40, 67925 LED12DP30R27/15, 67927 LED12DPR927/40, 68387 LED12DP3LR930/15, 68388 LED12DP3LR930/25, 68389 LED12DP3LR930/40, 68390 LED12DP3LR927/15, 68391 LED12DP3LR927/25, 68392 LED12DP3LR927/40

Other Model Numbers:

**Manufacturer's Description**

|                    |                      |                |                                      |
|--------------------|----------------------|----------------|--------------------------------------|
| Type of device:    | <u>LED 12W PAR30</u> | Control Type:  | <u>Forward Phase (including MLV)</u> |
| Operating voltage: | <u>120V</u>          | Dimming Range: | <u>20-100%</u>                       |
| Input Power:       | <u>12 W</u>          | Output Power:  | <u>N/A</u>                           |
| Input Current:     | <u>0.14 A</u>        | Lumen Output:  | <u>Varies</u>                        |
| Input Frequency:   | <u>60Hz</u>          |                |                                      |

**Lutron Test Results**

Date Tested: 5-Jun-12  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not compatible, based on our testing.*

| Product                          | Model Number  | Fixtures per Dimmer |         | Measured Dimming Range <sup>(1)</sup> |          | Perceived Low End <sup>(2)</sup> | Comments  |
|----------------------------------|---|---------------------|---------|---------------------------------------|----------|----------------------------------|---|
|                                  |   | Minimum             | Maximum | Low End                               | High End |                                  |   |
| <i>Wallbox Dimmers</i>           |   |                     |         |                                       |          |                                  |   |
| Maestro RF                       | MRF2-6ND  | 1                   | 12      | 9%                                    | 92%      | 30%                              |   |
| <i>Commercial Systems</i>        |   |                     |         |                                       |          |                                  |   |
| Panel Module                     | HW/LP-RPM-4A-120  | 1                   | 44      | 10%                                   | 98%      | 32%                              | Set load type to FP. Rating is per channel; total per module is 70. |
| Panel Module                     | HW/LP-RPM-4U-120  | 1                   | 71      | 10%                                   | 95%      | 32%                              | Rating is per channel; total per module is 71.                      |
| Grafik QS                        | Grafik Eye QS Main Unit Family  | 1                   | 29      | 10%                                   | 99%      | 31%                              | Rating is per output; total per Main Unit is 72                     |
| Panel Module                     | GP (Harrier) Card   | 1                   | 71      | 10%                                   | 98%      | 32%                              | Rating is per output.   |
| <i>Residential Systems</i>       |   |                     |         |                                       |          |                                  |   |
| RadioRA 2                        | RRD-10ND  | 1                   | 12      | 9%                                    | 92%      | 30%                              |   |
| HomeWorks QS                     | HQRD-6ND  | 1                   | 12      | 9%                                    | 92%      | 30%                              |   |
| HomeWorks QS                     | HQRD-10ND   | 1                   | 12      | 9%                                    | 92%      | 30%                              |   |
| RadioRA 2                        | RRD-6NA   | 1                   | 12      | 8%                                    | 92%      | 29%                              | Set load type to forward phase.                                     |
| Homeworks QS                     | HQRD-6NA  | 1                   | 12      | 8%                                    | 92%      | 29%                              | Set load type to forward phase.                                     |
| Panel Module                     | HW/LP-RPM-4A-120  | 1                   | 44      | 10%                                   | 98%      | 32%                              | Set load type to FP. Rating is per channel; total per module is 70. |
| Panel Module                     | HW/LP-RPM-4U-120  | 1                   | 71      | 10%                                   | 95%      | 32%                              | Rating is per channel; total per module is 71.                      |
| Grafik QS                        | Grafik Eye QS Main Unit Family  | 1                   | 29      | 10%                                   | 99%      | 31%                              | Rating is per output; total per Main Unit is 72                     |
| Panel Module                     | GP (Harrier) Card   | 1                   | 71      | 10%                                   | 98%      | 32%                              | Rating is per output.   |
| <i>Interfaces <sup>(3)</sup></i> |   |                     |         |                                       |          |                                  |   |
| <i>No applicable results</i>     |   |                     |         |                                       |          |                                  |   |
| Notes:                           | (1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability<br>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook<br>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly |                     |         |                                       |          |                                  |   |

Test Comments: Performance verified with up to 12 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Minimum light level set at ~10% to prevent dip in low-end light level. Low end trim required. Slight buzzing.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or [leds@lutron.com](mailto:leds@lutron.com).  
This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at [www.lutron.com/LEDtool](http://www.lutron.com/LEDtool).*