



# LUTRON® Product Report Card

ID 1113

**Manufacturer:** GE Lighting  
**Model Number Tested:** LED11DA19V2  
**Other Model Numbers:** PC89885, PC89983, PC89888, PC94159

**Manufacturer's Description**

Type of device: LED 11W A-Lamp  
 Operating voltage: 120V  
 Input Power: 11.0 W  
 Input Current: 0.13 A  
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control  
 Dimming Range: 20-100  
 Output Power: Not Specified  
 Lumen Output: Not Specified

**Lutron Test Results**

Date Tested: 12-Sep-13  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not recommended, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Credenza	TTCL-100	1	9	18%	85%	43%	Performance verified with up to 5 fixtures.
Maestro Wireless	MRF2-6ND	1	13	20%	90%	44%	
Maestro Sensor	MSCL-OP153M (T2)*/ MSCL-VP153M (T2)*	1	13	18%	85%	42%	
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	13	8%	86%	28%	
Panel Module	HW/LP-RPM-4A-120	1	96	8%	90%	28%	Set load type to RP. Rating is per channel; total per module is 153.
Panel Module	HW/LP-RPM-4U-120	1	44	8%	95%	29%	Rating is per channel; total per module is 44.
Grafik QS	Grafik Eye QS Main Unit Family	1	18	7%	97%	26%	Rating is per output; total quantity per Main Unit is 45.
Panel Module	GP (Harrier) Card	1	44	7%	97%	26%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	18	7%	97%	26%	Rating is per output; total quantity per Main Unit is 27, 45, and 45 for 2, 4, and 6 zone units, respectively.
<i>Residential Systems</i>							
RadioRA 2	RRD-10ND	1	13	20%	90%	44%	
HomeWorks QS	HQRD-6ND	1	13	20%	90%	44%	
HomeWorks QS	HQRD-10ND	1	13	20%	90%	44%	
RadioRA 2	RRD-6NA	2	13	19%	86%	43%	Load type not selectable. Evaluated in FP.
Homeworks QS	HQRD-6NA	2	13	19%	86%	43%	Load type not selectable. Evaluated in FP.
HomeWorks	HxD-6ND	1	13	8%	86%	28%	
Panel Module	HW/LP-RPM-4A-120	1	96	8%	90%	28%	Set load type to RP. Rating is per channel; total per module is 153.
Panel Module	HW/LP-RPM-4U-120	1	44	8%	95%	29%	Rating is per channel; total per module is 44.
Grafik QS	Grafik Eye QS Main Unit Family	1	18	7%	97%	26%	Rating is per output; total quantity per Main Unit is 45.

Panel Module	GP (Harrier) Card	1	44	7%	97%	26%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	18	7%	97%	26%	Rating is per output; total quantity per Main Unit is 27, 45, and 45 for 2, 4, and 6 zone units, respectively.
<i>Interfaces</i> <sup>(3)</sup>							
	PHPM-PA with Grafik Eye QS Main Unit	1	154	7%	93%	26%	
	PHPM-WBX with 3-wire fluorescent control	1	154	7%	93%	26%	
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; ( ) means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 14 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at [www.lutron.com/LEDtool](http://www.lutron.com/LEDtool).*