



LUTRON® Product Report Card

ID 857

Manufacturer: GE
Model Number Tested: 65386 LED 13DA19/830
Other Model Numbers: 64129 LED13DA19/830/BK, 64130 LED13DA19/830/TP, 69255 LED13DA19/827

Manufacturer's Description

Type of device:	<u>LED 13W White frosted A-lamp</u>	Control Type:	<u>Forward Phase (including MLV)</u>
Operating voltage:	<u>120V</u>	Dimming Range:	<u>10-100%</u>
Input Power:	<u>13.0 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.11 A</u>	Lumen Output:	<u>800</u>
Input Frequency:	<u>50Hz/60Hz</u>		

Lutron Test Results

Date Tested: 21-Nov-12
 Test Voltage: 120 V
 Test Notes: None

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not compatible, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Maestro	MACL-153M	1	11	11%	90%	33%	
Credenza	TTCL-100	1	7	10%	97%	31%	Performance verified with up to 5 fixtures.
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	85	17%	99%	41%	Set load type to FP. Rating is per channel; total per module is 136.
Panel Module	HW/LP-RPM-4U-120	1	137	15%	96%	39%	Rating is per channel; total per module is 137.
Grafik QS	Grafik Eye QS Main Unit Family	1	57	19%	99%	43%	Rating is per output; total per Main Unit is 142.
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	85	17%	99%	41%	Set load type to FP. Rating is per channel; total per module is 136.
Panel Module	HW/LP-RPM-4U-120	1	137	15%	96%	39%	Rating is per channel; total per module is 137.
Grafik QS	Grafik Eye QS Main Unit Family	1	57	19%	99%	43%	Rating is per output; total per Main Unit is 142.
<i>Interfaces ⁽³⁾</i>							
<i>No applicable results</i>							
Notes:	(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 12 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.
 This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*