



LUTRON® Product Report Card

ID 1216

Manufacturer: GREEN CREATIVE
Model Number Tested: 9.5A19G3DIM/830WB
Other Model Numbers: 9.5A19G3DIM/XXXWB (XXX means 824-965 which indicate CRI and color Temperature)

Manufacturer's Description

Type of device:	<u>LED 9.5W A19</u>	Control Type:	<u>Forward and Reverse Phase Control</u>
Operating voltage:	<u>120V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>9.5 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.09 A</u>	Lumen Output:	<u>820</u>
Input Frequency:	<u>60Hz</u>		

Lutron Test Results

Date Tested: 14-Nov-13
 Test Voltage: 120 V
 Test Notes: None

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
Wallbox Dimmers							
Credenza	TTCL-100	1	10	14%	87%	37%	Performance verified with up to 5 fixtures.
Maestro Wireless	MRF2-6ND	1	15	20%	95%	45%	Start time in excess of 1 second.
Commercial Systems							
Stanza	SZ-6ND	1	15	7%	95%	26%	
Panel Module	HW/LP-RPM-4A-120	1	122	18%	96%	43%	Set load type to RP. Rating is per channel; total per module is 195.
Panel Module	HW/LP-RPM-4U-120	1	50	11%	98%	34%	Rating is per channel; total per module is 50.
Grafik QS	Grafik Eye QS Main Unit Family	1	21	8%	100%	28%	Rating is per output; total quantity per Main Unit is 52.
Panel Module	GP (Harrier) Card	1	50	17%	99%	41%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	21	8%	100%	28%	Rating is per output; total quantity per Main Unit is 31, 52, and 52 for 2, 4, and 6 zone units, respectively.
Residential Systems							
RadioRA 2	RRD-10ND	1	15	20%	95%	45%	Start time in excess of 1 second.
HomeWorks QS	HQRD-6ND	1	15	20%	95%	45%	Start time in excess of 1 second.
HomeWorks QS	HQRD-10ND	1	15	20%	95%	45%	Start time in excess of 1 second.
RadioRA 2	RRD-6NA	1	15	20%	96%	45%	Start time in excess of 1 second. Load type not selectable. Evaluated in FP.
Homeworks QS	HQRD-6NA	1	15	20%	96%	45%	Start time in excess of 1 second. Load type not selectable. Evaluated in FP.
HomeWorks	HxD-6ND	1	15	7%	95%	26%	
Panel Module	HW/LP-RPM-4A-120	1	122	18%	96%	43%	Set load type to RP. Rating is per channel; total per module is 195.
Panel Module	HW/LP-RPM-4U-120	1	50	11%	98%	34%	Rating is per channel; total per module is 50.

Grafik QS	Grafik Eye QS Main Unit Family	1	21	8%	100%	28%	Rating is per output; total quantity per Main Unit is 52.
Panel Module	GP (Harrier) Card	1	50	17%	99%	41%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	21	8%	100%	28%	Rating is per output; total quantity per Main Unit is 31, 52, and 52 for 2, 4, and 6 zone units, respectively.
Interfaces⁽³⁾							
	PHPM-PA with Grafik Eye QS Main Unit	1	196	20%	100%	45%	
	PHPM-WBX with 3-wire fluorescent control	1	196	20%	100%	45%	
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 15 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.