



# LUTRON® Product Report Card

ID 1218

**Manufacturer:** Green Creative  
**Model Number Tested:** 14PAR30G3DIM/830FL40  
**Other Model Numbers:** 14PAR30G3DIM/XXXXYY

**Manufacturer's Description**

Type of device: LED PAR30 14W  
 Operating voltage: 120V  
 Input Power: 14.0 W  
 Input Current: 0.13 A  
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control  
 Dimming Range: Not Specified  
 Output Power: Not Specified  
 Lumen Output: 850

**Lutron Test Results**

Date Tested: 25-Nov-13  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not recommended, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Maestro Wireless	MRF2-6ND	1	10	15%	93%	39%	Low end trim required.
Maestro Wireless	MRF2-6ELV	1	46	16%	91%	40%	Low end trim required. Load type not selectable. Evaluated in RP.
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	13	7%	91%	27%	Low end trim required.
Panel Module	HW/LP-RPM-4A-120	1	27	9%	99%	30%	High end and low end trim required. Set load type to FP. Rating is per channel; total per module is 43.
Panel Module	HW/LP-RPM-4U-120	1	44	9%	99%	31%	High end and low end trim required. Rating is per channel; total per module is 44.
Grafik QS	Grafik Eye QS Main Unit Family	1	18	9%	100%	31%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 45.
Panel Module	GP (Harrier) Card	1	44	10%	99%	31%	High end and low end trim required. Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	18	9%	100%	31%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 27, 45, and 45 for 2, 4, and 6 zone units, respectively.
<i>Residential Systems</i>							
RadioRA 2	RRD-10ND	1	10	15%	93%	39%	Low end trim required.
HomeWorks QS	HQRD-6ND	1	10	15%	93%	39%	Low end trim required.
HomeWorks QS	HQRD-10ND	1	10	15%	93%	39%	Low end trim required.
RadioRA 2	RRD-6NA	1	46	16%	91%	40%	Low end trim required. Load type not selectable. Evaluated in RP.
Homeworks QS	HQRD-6NA	1	46	16%	91%	40%	Low end trim required. Load type not selectable. Evaluated in RP.
HomeWorks	HxD-6ND	1	13	7%	91%	27%	Low end trim required.
Panel Module	HW/LP-RPM-4A-120	1	27	9%	99%	30%	High end and low end trim required. Set load type to FP. Rating is per channel; total per module is 43.

Panel Module	HW/LP-RPM-4U-120	1	44	9%	99%	31%	High end and low end trim required. Rating is per channel; total per module is 44.
Grafik QS	Grafik Eye QS Main Unit Family	1	18	9%	100%	31%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 45.
Panel Module	GP (Harrier) Card	1	44	10%	99%	31%	High end and low end trim required. Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	18	9%	100%	31%	High end and low end trim required. Rating is per output; total quantity per Main Unit is 27, 45, and 45 for 2, 4, and 6 zone units, respectively.
<b>Interfaces<sup>(3)</sup></b>							
	PHPM-PA with Grafik Eye QS Main Unit	1	137	14%	100%	38%	High end and low end trim required.
	PHPM-WBX with 3-wire fluorescent control	1	137	14%	100%	38%	High end and low end trim required.
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; ( ) means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 10 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*