

[No product image available]



ID: 3168

Product Report Card

Manufacturer: Luxna
Model Number Tested: LXFRD10WW
 Other Model Numbers: LXFRD10NW, LXFRD10CW

Manufacturer's Description

| | |
|---|--|
| Type of Device: <u>LED 10 W Downlight</u> | Control Type: <u>Forward and Reverse Phase Control</u> |
| Operating Voltage: <u>240</u> | Dimming Range: <u>Not Specified</u> |
| Input Power: <u>10 W</u> | Output Power: <u>10 W</u> |
| Input Current: <u>0.043 A</u> | Lumen Output: <u>Not Specified</u> |
| Input Frequency: <u>50 Hz</u> | Type/Shape: <u>Downlight</u> |
| | Base Type: <u>N/A</u> |

Lutron Test Results

Date Tested: 11/28/2017
 Test Voltage: 240 V
 Test Notes: Test results valid only at 240V and 50 Hz.

Lutron Recommended Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

| Product | Model Number | Control Type ⁽¹⁾ | Fixtures per Dimmer ⁽²⁾ | Measured Dimming Range ⁽³⁾ (Software Trim Settings) | | Perceived Low End ⁽⁴⁾ | Comments |
|---------------------------------|---|-----------------------------|------------------------------------|---|---------|----------------------------------|--|
| | | | | Min-Max | Low End | | |
| Commercial Systems | | | | | | | |
| Panel Module | GP (Harrier) Card | FP | 1 - 67 | 14% | 98% | 37% | Rating is per output. Use load type 2-1. |
| HomeWorks QS/ESN Phase Adaptive | LQSE-4A-D (Gen. 2)/QSNE-4A-D (Gen. 2) | RP | 1 - 24 | 16% | 97% | 39% | |
| HomeWorksQS/myRoom | LQSE-4A1-D/MQSE-4A1-D/MQSE-3A1/MQSE-2A1-D, 240V, RP | RP | 1 - 7 | 11% | 91% | 33% | |
| Grafik Integrale | GXI-3104 | RP | 1 - 22 | 13% | 95% | 36% | |
| Interfaces | | | | | | | |
| [none] | NGRX-ELVI-CE with Grafik Eye QS Main Unit, 240V | RP | 1 - 34 | 14% | 89% | 37% | |
| [none] | NGRX-PB-CE with Grafik Eye QS Main Unit, 240V | FP | 1 - 12 | 13% | 99% | 37% | |
| Residential Systems | | | | | | | |
| Panel Module | GP (Harrier) Card | FP | 1 - 67 | 14% | 98% | 37% | Rating is per output. Use load type 2-1. |
| HomeWorks QS/ESN Phase Adaptive | LQSE-4A-D (Gen. 2)/QSNE-4A-D (Gen. 2) | RP | 1 - 24 | 16% | 97% | 39% | |
| HomeWorksQS/myRoom | LQSE-4A1-D/MQSE-4A1-D/MQSE-3A1/MQSE-2A1-D, 240V, RP | RP | 1 - 7 | 11% | 91% | 33% | |
| WallBox Dimmers | | | | | | | |
| No applicable results | | | | | | | |

| Product | Model Number | Control Type | Fixtures per Dimmer | Measured Dimming Range (Software Trim Settings) | | Perceived Low End | Comments |
|---------|---|--------------|---------------------|---|----------|-------------------|----------|
| | | | Min-Max | Low End | High End | | |
| Notes: | <ul style="list-style-type: none"> * Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information. (1) Control types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details. (2) Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. (3) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability. Values are set to optimize performance, such as reducing dead travel, ensuring that fixtures turn on at low end, reducing turn-on time at low end, and trimming out instability. Software trim values are indicated in parentheses when applicable. (4) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. (5) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly. | | | | | | |

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.

This information was posted with the consent and cooperation of the device manufacturer. Please be aware that device manufacturers may modify their product at any time, without notice to Lutron, and therefore Lutron cannot ensure future compatibility. For more detailed and up to date fixture specifications, performance and/or any related recall information, visit the manufacturer's website. The latest Lutron test results can always be found at www.lutron.com/LEDtool.