



# LUTRON® Product Report Card

ID 707

**Manufacturer:** Maxlite  
**Model Number Tested:** SKP17DLED30  
**Other Model Numbers:** None

**Manufacturer's Description**

Type of device: LED Pancake shape short in height, diameter app Control Type: Forward and Reverse Phase Control  
 Operating voltage: 120V Dimming Range: Not Specified  
 Input Power: 17.0W Output Power: Not Specified  
 Input Current: Not Specified Lumen Output: Not Specified  
 Input Frequency: 60Hz

**Lutron Test Results**

Date Tested: 7-Sep-12  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not compatible, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Maestro RF	MRF2-6ND	1	8	20%	100%	44%	
Maestro RF	MRF2-6ELV	1	8	18%	97%	42%	Set load type to RP.
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	16	19%	98%	43%	High end trim required. Set load type to RP. Rating is per channel; total per module is 25.
Panel Module	HW/LP-RPM-4U-120	1	27	19%	99%	44%	High end trim required. Rating is per channel; total per module is 27.
<i>Residential Systems</i>							
RadioRA 2	RRD-10ND	1	8	20%	100%	44%	
HomeWorks QS	HQRD-6ND	1	8	20%	100%	44%	
HomeWorks QS	HQRD-10ND	1	8	20%	100%	44%	
RadioRA 2	RRD-6NA	1	8	18%	97%	42%	Set load type to RP.
HomeWorks QS	HQRD-6NA	1	8	18%	97%	42%	Set load type to RP.
Panel Module	HW/LP-RPM-4A-120	1	16	19%	98%	43%	High end trim required. Set load type to RP. Rating is per channel; total per module is 25.
Panel Module	HW/LP-RPM-4U-120	1	27	19%	99%	44%	High end trim required. Rating is per channel; total per module is 27.
<i>Interfaces <sup>(3)</sup></i>							
<i>No applicable results</i>							
Notes:	(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 8 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Low end trim required with all controls. Some steppy dimming and high end dead travel may be observed.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*