

Manufacturer: Orluna
Model Number Tested: Power LED PCC70018TD

Other Model Numbers: None

Manufacturer's Description

Type of device:	<u>LED 18 W Downlight</u>	Control Type:	<u>Reverse Phase</u>
Operating voltage:	<u>240V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>18.0 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.11 A</u>	Lumen Output:	<u>Not Specified</u>
Input Frequency:	<u>50Hz</u>	Type/Shape:	<u>Downlight</u>
		Base Type:	<u>N/A</u>

Lutron Test Results

Date Tested: 17-Feb-14
 Test Voltage: 240 V
 Test Notes: Test results valid only with a Power LED PCC70018TD transformer and 1 lamp per transformer. Test results valid only at 240V

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments ⁽³⁾
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
<i>No applicable results</i>							
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-230	1	106	9%	98%	29%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 106.
Homeworks QS/ESN Phase Adaptive	LQSE-4A-D ()*/QSNE-4A-D ()*	1	27	5%	97%	22%	High end and low end trim required. Set load type to RP. Rating is for Zone 1. Rating for Zones 2-4 is 27.
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4A-230	1	106	9%	98%	29%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 106.
Homeworks QS/ESN Phase Adaptive	LQSE-4A-D ()*/QSNE-4A-D ()*	1	27	5%	97%	22%	High end and low end trim required. Set load type to RP. Rating is for Zone 1. Rating for Zones 2-4 is 27.
<i>Interfaces⁽⁴⁾</i>							
	NGRX-ELVI-CE	1	66	7%	96%	27%	High end and low end trim required.
Notes:	* Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information (1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Load types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details. (4) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Performance verified with up to 10 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Test results valid only with a Power LED PCC70018TD transformer and 1 lamp per transformer. Test results valid only at 240V 50Hz.

Test Comments:

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.