



LUTRON® Product Report Card

ID 1094

Manufacturer: Philips
Model Number Tested: 9290002426
Other Model Numbers: None

Manufacturer's Description

Type of device: LED A21 15W
 Operating voltage: 120V
 Input Power: 15.0 W
 Input Current: 0.19 A
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumen Output: 1180

Lutron Test Results

Date Tested: 3-Sep-13
 Test Voltage: 120 V
 Test Notes: Performance may differ on controls built prior to 2013.

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Diva/ Skylark/ Skylark Contour/ Ariadni/ Toggler	C-L wall-mount dimmers (T1)*	1	10	4%	100%	20%	
Maestro	MACL-153M (L)*	1	10	4%	91%	21%	
Maestro Sensor	MSCL-OP153M (T2)*/ MSCL-VP153M (T2)*	1	10	4%	100%	20%	
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	15	4%	99%	19%	
Panel Module	HW/LP-RPM-4A-120	1	30	5%	99%	23%	Set load type to FP. Rating is per channel; total per module is 48.
Panel Module	HW/LP-RPM-4U-120	1	48	4%	99%	20%	Rating is per channel; total per module is 48.
Grafik QS	Grafik Eye QS Main Unit Family	1	20	4%	99%	20%	Rating is per output; total quantity per Main Unit is 50.
Panel Module	GP (Harrier) Card	1	48	5%	99%	22%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	20	4%	99%	20%	Rating is per output; total quantity per Main Unit is 30, 50, and 50 for 2, 4, and 6 zone units, respectively.
<i>Residential Systems</i>							
HomeWorks	HxD-6ND	1	15	4%	99%	19%	
Panel Module	HW/LP-RPM-4A-120	1	30	5%	99%	23%	Set load type to FP. Rating is per channel; total per module is 48.
Panel Module	HW/LP-RPM-4U-120	1	48	4%	99%	20%	Rating is per channel; total per module is 48.
Grafik QS	Grafik Eye QS Main Unit Family	1	20	4%	99%	20%	Rating is per output; total quantity per Main Unit is 50.
Panel Module	GP (Harrier) Card	1	48	5%	99%	22%	Rating is per output.

Grafik Eye 3000	Grafik Eye 3000 Family	1	20	4%	99%	20%	Rating is per output; total quantity per Main Unit is 30, 50, and 50 for 2, 4, and 6 zone units, respectively.
<i>Interfaces⁽³⁾</i>							
<i>No applicable results</i>							
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 12 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. May experience stepy dimming. Performance may differ on controls built prior to 2013.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.
This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*