

**Manufacturer:** Philips  
**Model Number Tested:** 9290002078  
**Other Model Numbers:** None

**Manufacturer's Description**

Type of device: LED EnduraLED RDL6 15w  
 Operating voltage: 120V  
 Input Power: 15.0W  
 Input Current: 0.18 A  
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control  
 Dimming Range: Not Specified  
 Output Power: Not Specified  
 Lumen Output: 800

**Lutron Test Results**

Date Tested: 5-Sep-13  
 Test Voltage: 120 V  
 Test Notes: None

**Lutron Recommended Compatible Products**

*Lutron products not in this list can be considered to be not recommended, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<b>Wallbox Dimmers</b>							
Diva/ Skylark/ Skylark Contour/ Ariadni/ Toggler	C-L wall-mount dimmers (T1)*	1	10	5%	100%	23%	
Maestro	MACL-153M (L)*	1	10	6%	96%	25%	
Maestro Wireless	MRF2-6ND	1	10	7%	100%	26%	May experience delayed start time of lamps at low end.
Maestro Sensor	MSCL-OP153M (T2)*/ MSCL-VP153M (T2)*	1	10	5%	100%	23%	
<b>Commercial Systems</b>							
Stanza	SZ-6ND	1	15	2%	99%	16%	
Panel Module	HW/LP-RPM-4A-120	1	31	6%	99%	24%	Set load type to RP. Rating is per channel; total per module is 49.
Panel Module	HW/LP-RPM-4U-120	1	49	5%	99%	23%	Rating is per channel; total per module is 49.
Grafik QS	Grafik Eye QS Main Unit Family	1	20	5%	100%	23%	Rating is per output; total quantity per Main Unit is 50.
Panel Module	GP (Harrier) Card	1	49	9%	100%	30%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	20	5%	100%	23%	Rating is per output; total quantity per Main Unit is 30, 50, and 50 for 2, 4, and 6 zone units, respectively.
<b>Residential Systems</b>							
RadioRA 2	RRD-10ND	1	10	7%	100%	26%	May experience delayed start time of lamps at low end.
HomeWorks QS	HQRD-6ND	1	10	7%	100%	26%	May experience delayed start time of lamps at low end.
HomeWorks QS	HQRD-10ND	1	10	7%	100%	26%	May experience delayed start time of lamps at low end.
HomeWorks	HxD-6ND	1	15	2%	99%	16%	
Panel Module	HW/LP-RPM-4A-120	1	31	6%	99%	24%	Set load type to RP. Rating is per channel; total per module is 49.

Panel Module	HW/LP-RPM-4U-120	1	49	5%	99%	23%	Rating is per channel; total per module is 49.
Grafik QS	Grafik Eye QS Main Unit Family	1	20	5%	100%	23%	Rating is per output; total quantity per Main Unit is 50.
Panel Module	GP (Harrier) Card	1	49	9%	100%	30%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	1	20	5%	100%	23%	Rating is per output; total quantity per Main Unit is 30, 50, and 50 for 2, 4, and 6 zone units, respectively.
<b>Interfaces<sup>(3)</sup></b>							
	PHPM-PA with Grafik Eye QS Main Unit	1	49	9%	93%	30%	
	PHPM-WBX with 3-wire fluorescent control	1	49	9%	93%	30%	
Notes:	<p>* Identical model numbers with different compatibility codes may have different performance; ( ) means there is no compatibility code assigned; contact technical support for additional information</p> <p>(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability</p> <p>(2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook</p> <p>(3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly</p>						

Test Comments: Performance verified with up to 10 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. May experience steppy dimming with most controls.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*