



LUTRON® Product Report Card

ID 692

Manufacturer: Philips Lighting Company
Model Number Tested: 17E26A21D
Other Model Numbers: None

Manufacturer's Description

Type of device: 17W A21 Endura LED
 Operating voltage: 120V
 Input Power: 17.0 W
 Input Current: 0.20 A
 Input Frequency: 60Hz

Control Type: Forward and Reverse Phase Control
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumen Output: Not Specified

Lutron Test Results

Date Tested: 17-Oct-12
 Test Voltage: 120 V
 Test Notes: None

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not compatible, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Maestro RF	MRF2-6ND	1	8	3%	100%	18%	
Maestro Wireless	MRF2-3LD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
Maestro Wireless	MRF2-3PD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
<i>Commercial Systems</i>							
Stanza	SZ-6ND	1	10	2%	95%	14%	High end trim recommended.
Panel Module	HW/LP-RPM-4A-120	1	21	3%	98%	16%	High end and low end trim required. Set load type to FP. Rating is per channel; total per module is 33.
Panel Module	HW/LP-RPM-4U-120	1	33	3%	99%	18%	High end and low end trim required. Rating is per channel; total per module is 33.
Grafik QS	Grafik Eye QS Main Unit Family	1	14	3%	100%	18%	Rating is per output; total per Main Unit is 35.
Panel Module	GP (Harrier) Card	1	33	5%	100%	22%	High end and low end trim required. Rating is per output.
<i>Residential Systems</i>							
RadioRA 2	RRD-10ND	1	8	3%	100%	18%	
HomeWorks QS	HQRD-6ND	1	8	3%	100%	18%	
HomeWorks QS	HQRD-10ND	1	8	3%	100%	18%	
RadioRA 2	RRD-6NA	1	8	3%	95%	18%	Low end trim required. Set load type to FP.
Homeworks QS	HQRD-6NA	1	8	3%	95%	18%	Low end trim required. Set load type to FP.
HomeWorks	HxD-6ND	1	10	2%	95%	14%	High end trim recommended.
RadioRA 2	RRD-3LD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
Homeworks QS	HQR-3LD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
RadioRa 2	RRD-3PD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
Homeworks QS	HQR-3PD	1	5	1%	100%	12%	Performance verified with up to 5 fixtures.
Panel Module	HW/LP-RPM-4A-120	1	21	3%	98%	16%	High end and low end trim required. Set load type to FP. Rating is per channel; total per module is 33.

Panel Module	HW/LP-RPM-4U-120	1	33	3%	99%	18%	High end and low end trim required. Rating is per channel; total per module is 33.
Grafik QS	Grafik Eye QS Main Unit Family	1	14	3%	100%	18%	Rating is per output; total per Main Unit is 35.
Panel Module	GP (Harrier) Card	1	33	5%	100%	22%	High end and low end trim required. Rating is per output.
<i>Interfaces⁽³⁾</i>							
	PHPM-PA with Grafik Eye QS Main Unit	1	34	4%	100%	20%	
	PHPM-WBX with 3-wire fluorescent control	1	34	4%	100%	20%	
Notes:	(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 8 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Steppy dimming may be observed.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.
This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*