



# LUTRON® Product Report Card

ID 793

Manufacturer: Philips  
 Model Number Tested: Award Winning LED Bulb, A-lamp 940 lumens 10W  
 Other Model Numbers: None

### Manufacturer's Description

Type of device: 940Lumens 10W (9290002097) 2700k Control Type: Unspecified Phase Control  
 Operating voltage: 120V Dimming Range: Not Specified  
 Input Power: 10 W Output Power: Not Specified  
 Input Current: 0.11 A Lumen Output: 940  
 Input Frequency: 60Hz

### Lutron Test Results

Date Tested: 28-Aug-12  
 Figure of Merit: N/A  
 Test Voltage: 120 V  
 Test Notes: None

### Lutron Recommended Compatible Products

*Lutron products not in this list can be considered to be not compatible, based on our testing.*

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range <sup>(1)</sup>		Perceived Low End <sup>(2)</sup>	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
<i>No applicable results</i>							
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	12	2%	88%	16%	
Panel Module	HW/LP-RPM-4U-120	1	13	2%	95%	14%	High end trim required.
Panel Module	GP (Harrier) Card	1	14	6%	100%	24%	
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	12	2%	88%	16%	
Panel Module	HW/LP-RPM-4U-120	1	13	2%	95%	14%	High end trim required.
HomeWorks	HxD-6ND	2	4	12%	96%	35%	2 lamps minimum. High end trim required.
HomeWorks	HxD-5NE	1	5	2%	95%	14%	
Panel Module	GP (Harrier) Card	1	14	6%	100%	24%	
RadioRA 2	RRD-10ND	1	7	2%	99%	15%	
RadioRA 2	RRD-6NA	1	6	2%	94%	14%	Flicker when turning off.
<i>Interfaces <sup>(3)</sup></i>							
	PHPM-WBX with DVF-103P	1	20	5%	100%	23%	
	PHPM-PA with QSG-6D	1	20	3%	100%	17%	
Notes:	(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 14 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. Steppy dimming may be seen. May flicker when turning off. Low end trim required for all controls.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com. This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*