



LUTRON® Product Report Card

ID 1169

Manufacturer: Sylvania
Model Number Tested: LED7MR16-DIM-930-FL36P
Other Model Numbers: None

Manufacturer's Description

Type of device:	<u>ELV w/ LED MR16 12V 7W</u>	Control Type:	<u>Reverse Phase</u>
Operating voltage:	<u>120V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>7.0 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.67 A</u>	Lumen Output:	<u>400</u>
Input Frequency:	<u>60Hz</u>		

Lutron Test Results

Date Tested: 24-Oct-13
 Test Voltage: 100 V
 Test Notes: Results valid only with Ligttech LET60LW and 1 lamp per transformer.

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
Vierti	VTELV-600M	1	58	20%	99%	44%	Low end trim required.
Nova T*	NTELV-600	1	58	15%	98%	39%	
Nova	NELV-450	1	43	15%	98%	39%	
Skylark Contour/ Lyneo LX	CTELV-303P LXELV-603PL	1	29	7%	94%	27%	
Diva/ Skylark	DVELV-300P SELV-300P	1	29	7%	95%	26%	
Maestro	MAELV-600	1	58	11%	98%	34%	
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	116	15%	97%	39%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 185.
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4A-120	1	116	15%	97%	39%	High end and low end trim required. Set load type to RP. Rating is per channel; total per module is 185.
<i>Interfaces⁽³⁾</i>							
	PHPM-PA with Grafik Eye QS Main Unit	1	155	20%	100%	45%	High end and low end trim required.
	PHPM-WBX with 3-wire fluorescent control	1	155	20%	100%	45%	High end and low end trim required.
Notes:	* Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information (1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 5 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.
 This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*