



LUTRON® Product Report Card

ID 1235

Manufacturer: Havells Sylvania Europe LTD.
Model Number Tested: ToLEDo+ GLS DIM 12W 806LM 827 E27 SL
Other Model Numbers: 0026428

Manufacturer's Description

Type of device:	<u>LED 12W A60</u>	Control Type:	<u>Forward and Reverse Phase Control</u>
Operating voltage:	<u>240V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>12.0 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>0.07 A</u>	Lumen Output:	<u>806 lm</u>
Input Frequency:	<u>50Hz</u>	Type/Shape:	<u>A60</u>
		Base Type:	<u>E27</u>

Lutron Test Results

Date Tested: 6-Dec-13
 Test Voltage: 240 V
 Test Notes: Test results valid only at 240V 50Hz.

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments ⁽³⁾
		Minimum	Maximum	Low End	High End		
<i>Wallbox Dimmers</i>							
<i>No applicable results</i>							
<i>Commercial Systems</i>							
Panel Module	HW/LP-RPM-4A-230	1	73	11%	99%	33%	Set load type to RP. Rating is per channel; total per module is 73.
Grafik QS	Grafik Eye QS Main Unit Family, 240V	2	17	8%	93%	28%	Rating is per output; total quantity per Main Unit is 51/68/78 for 3/4/6-Zone units, respectively.
Grafik Eye	GRX-3104-CE	1	27	8%	92%	28%	Rating is per output; total quantity per Main Unit is 54/77/77/77 for 2/3/4/6-Zone units, respectively.
<i>Residential Systems</i>							
Panel Module	HW/LP-RPM-4A-230	1	73	11%	99%	33%	Set load type to RP. Rating is per channel; total per module is 73.
<i>Interfaces⁽⁴⁾</i>							
	NGRX-ELVI-CE	1	45	10%	96%	32%	
	NGRX-PB-CE	1	41	10%	98%	31%	
Notes:	* Identical model numbers with different compatibility codes may have different performance; (L) means there is no compatibility code assigned; contact technical support for additional information (1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Load types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details. (4) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: Performance verified with up to 12 fixtures per control. Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.
 This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*