



Product Report Card

Manufacturer: Utilitech

Model

Number LCFCDM/300/LED

Tested:

LCFFDM/300/LED, LEFCDM/300/LED, LA15DM/CL/300/LED, LA15DM/IF/300/LED, LA15DMC/CL/300/LED,

Other Model LG161/2DM/CL/300/LED, LG161/2DM/IF/300/LED, LGMDM/CL/300/LED, LG161/2DM/IF/LED, CFF/DM/300/LED,

Numbers: CFCDM/300/LED/CAN, CFC/DM/300/LED, BPA15C/CL/DM/LED, BPA15/CL/DM/LED, LG1612DMIF300/LED,

BPG161/2CL/DM/LED

Manufacturer's Description

Type of Device: LED 4.8 W

Operating Voltage: 120

Input Power: 4.8 W

Input Current: 0.066 A

Input Frequency: 60 Hz

Control Type: Forward Phase

Dimming Range: Not Specified

Output Power: Not Specified

Lumen Output: 300 lm

Type/Shape:

Base Type: E12

Lutron Test Results

Date Tested 07/02/2014

Test Voltage 120 V

Test Notes Test results valid only at 120 V and 60 Hz.

Lutron Recommended Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Control Type ⁽¹⁾	Fixtures per Dimmer ⁽²⁾	Measured Dimming Range ⁽³⁾		Perceived Low End ⁽⁴⁾	Comments
				(Software Trim Settings)			
			Min-Max	Low End	High End		
Commercial Systems							
Stanza	SZ-6ND	FP	1 - 17	17%	97%	41%	Low & high end trim may be required.
Panel Module	HW/LP-RPM-4A-120	FP	1 - 19	19%	97%	44%	Low & high end trim may be required. Rating is per channel; total per module is 30.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 141	16%	96%	40%	Low & high end trim may be required. Rating is per channel; total per module is 141.
Grafik QS/Wallbox Power Module	Grafik Eye QS Main Unit Family/LQRJ-WPM-6P	FP	1 - 77	7%	98%	27%	Rating is per output; total quantity per Main Unit is 192.
Grafik Eye 3000/HomeWorks	Grafik Eye 3000 Family/HWI-WPM-6D-120	FP	1 - 77	7%	98%	27%	Rating is per output; total quantity per Main Unit is 115/144/192/192 for 2/3/4/6-Zone units, respectively.
Interfaces							
<i>No applicable results</i>							
Residential Systems							
HomeWorks	HxD-6ND	FP	1 - 17	17%	97%	41%	Low & high end trim may be required.
Panel Module	HW/LP-RPM-4A-120	FP	1 - 19	19%	97%	44%	Low & high end trim may be required. Rating is per channel; total per module is 30.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 141	16%	96%	40%	Low & high end trim may be required. Rating is per channel; total per module is 141.
Grafik QS/Wallbox Power Module	Grafik Eye QS Main Unit Family/LQRJ-WPM-6P	FP	1 - 77	7%	98%	27%	Rating is per output; total quantity per Main Unit is 192.

Product	Model Number	Control Type	Fixtures per Dimmer	Measured Dimming Range (Software Trim Settings)		Perceived Low End	Comments
			Min-Max	Low End	High End		
Grafik Eye 3000/HomeWorks	Grafik Eye 3000 Family/HWI-WPM-6D-120	FP	1 - 77	7%	98%	27%	Rating is per output; total quantity per Main Unit is 115/144/192/192 for 2/3/4/6-Zone units, respectively.

WallBox Dimmers

Diva/Skylark/Skylark Contour/Ariadni/Toggler/ Lumea	CL wall-mount dimmers (T1, T4)	FP	2 - 31	20%	97%	45%	Low & high end trim may be required.
Maestro	MACL-153M ()	FP	1 - 31	8%	99%	29%	
Maestro Sensor	MSCL-OP153M (T2)/MSCL-VP153M (T2)	FP	2 - 31	18%	98%	42%	Low & high end trim may be required.
Caseta Wireless	PD-6WCL (SD11)	FP	2 - 31	19%	98%	44%	

Notes:

- * Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information.
- (1) Control types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details.
- (2) Maximum Fixtures per Dimmer value represents the maximum safe loading of the control.
- (3) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability. Values are set to optimize performance, such as reducing dead travel, ensuring that fixtures turn on at low end, reducing turn-on time at low end, and trimming out instability. Software trim values are indicated in parentheses when applicable.
- (4) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook.
- (5) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly.

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.

This information was posted with the consent and cooperation of the device manufacturer. Please be aware that device manufacturers may modify their product at any time, without notice to Lutron, and therefore Lutron cannot ensure future compatibility. For more detailed and up to date fixture specifications, performance and/or any related recall information, visit the manufacturer's website. The latest Lutron test results can always be found at www.lutron.com/LEDtool.