



Product Report Card

Manufacturer: Utilitech
Model Number Tested: LMR16GU10DMLEDG2
 Other Model Numbers: (587048)

Manufacturer's Description

Type of Device: LED 5.5 W MR16
 Operating Voltage: 120
 Input Power: 5.5 W
 Input Current: 0.07 A
 Input Frequency: 60 Hz

Control Type: Forward and Reverse Phase Control
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumen Output: 350 lm
 Type/Shape: MR16
 Base Type: GU10

Lutron Test Results

Date Tested: 09/22/2015
 Test Voltage: 120 V
 Test Notes:

Lutron Recommended Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Control Type ⁽¹⁾	Fixtures per Dimmer ⁽²⁾	Measured Dimming Range ⁽³⁾ (Software Trim Settings)		Perceived Low End ⁽⁴⁾	Comments	
				Min-Max	Low End			High End
Commercial Systems								
Panel Module	HW/LP-RPM-4A-120	RP	1 - 35		12%	94%	35%	Rating is per channel; total per module is 56.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 126		16%	94%	40%	Rating is per channel; total per module is 126.
Interfaces								
[none]	PHPM-PAwith Grafik Eye QS Main Unit	RP	1 - 35		14%	94%	38%	
[none]	PHPM-WBXwith 3-wire fluorescent control	RP	1 - 35		14%	94%	38%	
Residential Systems								
RadioRA 2	RRD-10ND	FP	1 - 27		19%	94%	44%	Low end trim required.
HomeWorks QS	HQRD-6ND	FP	1 - 27		19%	94%	44%	Low end trim required.
HomeWorks QS	HQRD-10ND	FP	1 - 27		19%	94%	44%	Low end trim required.
Panel Module	HW/LP-RPM-4A-120	RP	1 - 35		12%	94%	35%	Rating is per channel; total per module is 56.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 126		16%	94%	40%	Rating is per channel; total per module is 126.
RadioRA 2	RRD-6CL (R3)	FP	1 - 27		8%	95%	28%	
HomeWorks QS	HQRD-6CL (H2)/HQRA-6CL (H2)	FP	1 - 27		8%	95%	28%	
WallBox Dimmers								
Diva/Skylark/Skylark Contour/Ariadni/Toggler/ Lumea	CL wall-mount dimmers (T1, T4, T5, T8)	FP	1 - 27		10%	95%	31%	Performance may vary with dimmers manufactured before 2013.
Maestro	MACL-153M (L)	FP	1 - 27		8%	91%	28%	
Maestro Wireless	MRF2-6ND	FP	1 - 27		19%	94%	44%	Low end trim required.
Maestro Sensor	MSCL-OP153M (T2)/MSCL-VP153M (T2)	FP	1 - 27		12%	93%	34%	

Product	Model Number	Control Type	Fixtures per Dimmer	Measured Dimming Range (Software Trim Settings)		Perceived Low End	Comments
			Min-Max	Low End	High End		
Caseta Wireless	PD-6WCL (SD11)	FP	1 - 27	11%	96%	33%	
Maestro Wireless	MRF2-6CL (M6)	FP	1 - 27	8%	95%	28%	
Diva/Ariadni C250W	250W CL dimmers (T5,T8)	FP	1 - 45	10%	95%	31%	
Nova T* 250W	NTCL-250 (T8)	FP	1 - 45	10%	95%	31%	
Notes:	<ul style="list-style-type: none"> * Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information. (1) Control types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details. (2) Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. (3) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability. Values are set to optimize performance, such as reducing dead travel, ensuring that fixtures turn on at low end, reducing turn-on time at low end, and trimming out instability. Software trim values are indicated in parentheses when applicable. (4) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. (5) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly. 						

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.

This information was posted with the consent and cooperation of the device manufacturer. Please be aware that device manufacturers may modify their product at any time, without notice to Lutron, and therefore Lutron cannot ensure future compatibility. For more detailed and up to date fixture specifications, performance and/or any related recall information, visit the manufacturer's website. The latest Lutron test results can always be found at www.lutron.com/LEDtool.