



Product Report Card

Manufacturer: Utilitech
Model Number Tested: LPAR38/1400/LEDG5
 Other Model Numbers:

Manufacturer's Description

Type of Device: LED 23 W PAR38
 Operating Voltage:
 Input Power: 23 W
 Input Current: 0.21 A
 Input Frequency: Not Specified
 Control Type: Forward Phase
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumen Output: 1400 lm
 Type/Shape: PAR38
 Base Type:

Lutron Test Results

Date Tested: 04/29/2013
 Test Voltage: 120 V
 Test Notes

Lutron Recommended Products

Lutron products not in this list can be considered to be not recommended, based on our testing.

Product	Model Number	Control Type ⁽¹⁾	Fixtures per Dimmer ⁽²⁾	Measured Dimming Range ⁽³⁾ (Software Trim Settings)		Perceived Low End ⁽⁴⁾	Comments
			Min-Max	Low End	High End		
Commercial Systems							
Panel Module	HW/LP-RPM-4A-120	FP	1 - 12	6%	96%	24%	Set load type to FP. Rating is per channel; total per module is 19.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 19	5%	96%	22%	Rating is per channel; total per module is 19.
Grafik QS	Grafik Eye QS Main Unit Family	FP	1 - 8	5%	97%	22%	Rating is per output; total quantity per Main Unit is 20.
Panel Module	GP (Harrier) Card	FP	1 - 19	5%	96%	23%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	FP	1 - 8	5%	97%	22%	Rating is per output; total quantity per Main Unit is 12, 20, and 20 for 2, 4, and 6 zone units, respectively.
Interfaces							
<i>No applicable results</i>							
Residential Systems							
RadioRA 2	RRD-10ND	FP	1 - 6	11%	91%	33%	
HomeWorks QS	HQRD-6ND	FP	1 - 6	11%	91%	33%	
HomeWorks QS	HQRD-10ND	FP	1 - 6	11%	91%	33%	
Panel Module	HW/LP-RPM-4A-120	FP	1 - 12	6%	96%	24%	Set load type to FP. Rating is per channel; total per module is 19.
Panel Module	HW/LP-RPM-4U-120	FP	1 - 19	5%	96%	22%	Rating is per channel; total per module is 19.
Grafik QS	Grafik Eye QS Main Unit Family	FP	1 - 8	5%	97%	22%	Rating is per output; total quantity per Main Unit is 20.
Panel Module	GP (Harrier) Card	FP	1 - 19	5%	96%	23%	Rating is per output.
Grafik Eye 3000	Grafik Eye 3000 Family	FP	1 - 8	5%	97%	22%	Rating is per output; total quantity per Main Unit is 12, 20, and 20 for 2, 4, and 6 zone units, respectively.
WallBox Dimmers							
Diva/Skylark Contour/Ariadni/Toggler	CL wall-mount dimmers (L)	FP	1 - 6	4%	86%	20%	

Product	Model Number	Control Type	Fixtures per Dimmer	Measured Dimming Range (Software Trim Settings)		Perceived Low End	Comments
			Min-Max	Low End	High End		
Diva/Skylark/Skylark Contour/Ariadni/Toggler/ Lumea	CL wall-mount dimmers (T1)	FP	1 - 6	11%	88%	34%	
Maestro	MACL-153M ()	FP	1 - 6	4%	85%	20%	
Maestro Wireless	MRF2-6ND	FP	1 - 6	11%	91%	33%	
Maestro Sensor	MSCL-OP153M (T2)/MSCL-VP153M (T2)	FP	1 - 6	9%	88%	30%	
Notes:	<ul style="list-style-type: none"> • * Identical model numbers with different compatibility codes may have different performance; () means there is no compatibility code assigned; contact technical support for additional information. • (1) Control types of FP and RP represent Forward Phase and Reverse Phase, respectively. See product literature for details. • (2) Maximum Fixtures per Dimmer value represents the maximum safe loading of the control. • (3) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability. Values are set to optimize performance, such as reducing dead travel, ensuring that fixtures turn on at low end, reducing turn-on time at low end, and trimming out instability. Software trim values are indicated in parentheses when applicable. • (4) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. • (5) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly. 						

For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com.

This information was posted with the consent and cooperation of the device manufacturer. Please be aware that device manufacturers may modify their product at any time, without notice to Lutron, and therefore Lutron cannot ensure future compatibility. For more detailed and up to date fixture specifications, performance and/or any related recall information, visit the manufacturer's website. The latest Lutron test results can always be found at www.lutron.com/LEDtool.