



LUTRON®

Product Report Card

Manufacturer: Phillips
 Applicable Model Numbers: 92900017 1200/1300/1400

Manufacturer's Description

Type of Fixture: PAR38 Indoor Flood
 Operating Voltage: 120 VAC
 Input Power: 16 W
 Current: 185 mA
 Frequency: 60 Hz
 Control Types: Not Specified
 Dimming Range: Not Specified
 Equivalent Incandescent Output Power: 45 W
 Lumens: 650 lm (3000K)

Lutron Test Results

Date Tested: May 4, 2010
 Model Number Tested: EnduraLED PAR38 dimmable 120V 16W
 Smooth and Continuous: Yes
 Test Notes: None

Lutron Recommended Compatible Products

Product	Part Number	Fixtures per Dimmer	Measured Light Output Range ⁽¹⁾	Comments
RadioRA 2	RRD-10ND	1-16	4%-100%	Smooth and continuous
Homeworks	HWD-5NE	1-7	3%-100%	Smooth and continuous
	HWD-6NE	1-9	17%-100%	Smooth and continuous
	HW-RPM-4A-120	1-18 per output	8%-100%	Smooth and continuous Maximum of 29 fixtures
Commercial Systems	QSG-6P	1-14 per output	2%-100%	Smooth and continuous Maximum of 35 fixtures
	LP-RPM-4A-120	1-18 per output	8%-100%	Smooth and continuous Maximum of 29 fixtures
Interfaces	PHPM-WBX	1-29	7%-100%	Smooth and continuous

⁽¹⁾ Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full capability

Comments: Some dimmers may require a low-end trim adjustment. The ability to set the low-end trim is available on select 3-Wire Fluorescent dimmers, Homeworks, and Commercial Systems products. Refer to product documentation or www.lutron.com for details.

