



LUTRON®

Product Report Card

Manufacturer: Lighting Science Group
 Applicable Model Numbers: DFN 20 W27, DFN 20 NW, DFN 20 CW

Manufacturer's Description

Type of Fixture: PAR20 Flood
 Operating Voltage: 120 VAC
 Input Power: 7W
 Current: Not Specified
 Frequency: 60 Hz
 Control Types: MLV/Incandescent
 Dimming Range: Not Specified
 Output Power: Not Specified
 Lumens: 350

Lutron Test Results

Date Tested: May 27, 2010 (Updated October 15, 2010)
 Model Number Tested: DFN 20 WW FL
 Smooth and Continuous: Yes
 Test Notes: None

Lutron Recommended Compatible Products

Product	Part Number	Fixtures per Dimmer	Measured Light Output Range ⁽¹⁾	Comments
Diva	DVCL-153P	1-21	5%-95%	Low end trim required
Radio Ra	RRD-10ND	1-12	4%-95%	Low end trim required
Stanza	SZ-6ND	1-7	13%-92%	
Homeworks	HW-RPM-4A-120	1-91 per output	2%-95%	Maximum of 146 fixtures
	HxD-6ND	1-7	1%-95%	Low end trim required
Commercial Systems	120V Grafik Eye QS Main Unit	1-10 per output	1%-99%	Low end trim required Maximum of 25 fixtures
	LP-RPM-4A-120	1-91 per output	2%-95%	Maximum of 146 fixtures
Interfaces	PHPM-WBX or -PA	1-146	4%-99%	

⁽¹⁾ Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full capability

Comments: Some dimmers may require a low-end trim adjustment. The ability to set the low-end trim is available on select 3-Wire Fluorescent dimmers, Homeworks, and Commercial Systems products. Refer to product documentation or www.lutron.com for details.