

[Product Image]



LUTRON®

Product Report Card

Manufacturer: Sylvania
 Model Number Tested: LED10PAR30/DIM/SG
 Other Model Numbers: None

Manufacturer's Description

Type of device:	<u>LED 10W PAR 30</u>	Control Type:	<u>Unspecified Phase Control</u>
Operating voltage:	<u>120V</u>	Dimming Range:	<u>Not Specified</u>
Input Power:	<u>10 W</u>	Output Power:	<u>Not Specified</u>
Input Current:	<u>Not Specified</u>	Lumen Output:	<u>Not Specified</u>
Input Frequency:	<u>60Hz</u>		

Lutron Test Results

Date Tested: 16-Feb-11
 Figure of Merit: N/A
 Test Voltage: 120 V
 Test Notes: None

Lutron Recommended Compatible Products

Lutron products not in this list can be considered to be not compatible, based on our testing.

Product	Model Number	Fixtures per Dimmer		Measured Dimming Range ⁽¹⁾		Perceived Low End ⁽²⁾	Comments
		Minimum	Maximum	Low End	High End		
Wallbox Dimmers							
Diva C-L Skylark Contour C-L	DV(W)CL-153P CTCL-153P	1	15	5%	99%	23%	Minor buzzing
Maestro RF	MRF2-6ELV	1	12	4%	97%	19%	
Commercial Systems							
Panel Module	HW/LP-RPM-4A-120	1	25	6%	97%	24%	
Panel Module	HW/LP-RPM-4U-120	1	35	6%	97%	24%	
Grafik QS	Grafik Eye QS Main Unit Family	1	14	6%	95%	24%	Minor buzzing
Residential Systems							
Panel Module	HW/LP-RPM-4A-120	1	25	6%	97%	24%	
Panel Module	HW/LP-RPM-4U-120	1	35	6%	97%	24%	
HomeWorks	HxD-6ND	1	11	16%	100%	40%	Low end trim required
HomeWorks	HxD-5NE	1	10	7%	95%	26%	Minor buzzing
Grafik QS	Grafik Eye QS Main Unit Family	1	14	6%	95%	24%	Minor buzzing
RadioRA	RA-5NE	1	10	5%	94%	22%	Low end trim required
RadioRA 2	RRD-10ND	1	18	10%	98%	31%	
RadioRA 2	RRD-6NA	1	12	6%	99%	25%	
Interfaces ⁽³⁾							
	PHPM-WBX with DVF-103P	1	43	6%	97%	24%	
	PHPM-PA with QSG-6D	1	43	7%	98%	26%	
Notes:	(1) Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full rated capability (2) Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook (3) Interfaces have been tested with the listed control; any compatible dimmer may be used instead, but high end/low end light levels may vary slightly						

Test Comments: None

*For any questions on this report, please contact the Lutron LED Center of Excellence at 877-DIM-LED8 or leds@lutron.com
 This information was posted with the consent and cooperation of the device manufacturer. Latest test results can always be found at www.lutron.com/LEDtool.*