



Product Report Card

Manufacturer: Light Emitting Designs
 Applicable Model Numbers: LED-1666, LED-1667

Manufacturer's Description

Type of Fixture: Flood
 Operating Voltage: 120 VAC
 Input Power: 10W
 Current: Not Specified
 Frequency: Not Specified
 Control Types: MLV/Incandescent
 Dimming Range: Not Specified
 Output Power: 10W
 Lumens: 450 (soft white)/550 (daylight)

Lutron Test Results

Date Tested: June 11, 2010 Updated: Dec. 28, 2011
 Model Number Tested: R30-D10SCD
 Smooth and Continuous: Yes
 Test Notes: Testing completed at 120 VAC/60 Hz

Lutron Recommended Compatible Products

Product	Part Number	Fixtures per Dimmer	Measured Light Output Range ⁽¹⁾	Comments
Radio Ra2	RRD-10D	1-12	1%-98%	Smooth and continuous but flickers upon startup
Homeworks	HW-RPM-4A	1-70 per output	7%-93%	Smooth and continuous but uneven start timing occurs Maximum of 112 fixtures
Commercial Systems	QSG-6P	1-10 per output	3%-100%	Smooth and continuous Low end trim required Maximum of 25 fixtures
	LP-RPM-4A	1-70 per output	7%-93%	Smooth and continuous but uneven start timing occurs Maximum of 112 fixtures
Interfaces	PHPM-WBX	1-112	3%-98%	Smooth and continuous but uneven start timing occurs

⁽¹⁾ Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full capability

Comments: Some dimmers may require a low-end trim adjustment. The ability to set the low-end trim is available on select 3-Wire Fluorescent dimmers, Homeworks, and Commercial Systems products. Refer to product documentation or www.lutron.com for details