



LED Product Report Card

Manufacturer: Optiled
 Applicable Model Numbers: Dimmable PAR30 (1503050217)

Manufacturer's Description

Type of Fixture: Downlight
 Operating Voltage: 120 Vac
 Input Power: 13 W
 Current: Not Specified
 Frequency: Not Specified
 Control Types: Not Specified
 Dimming Range: Not Specified
 Output Power: N/A
 Lumens: 420

Lutron Test Results

Date Tested: August 26, 2009 Updated: Dec. 28, 2011
 Model Number Tested: PAR30
 Smooth and Continuous: Yes
 Test Notes:

Lutron Recommended Compatible Products

Product	Part Number	Fixtures per Dimmer	Measured Light Output Range ⁽¹⁾	Comments
RadioRA	RA-5NE	1 – 8	13% - 100%	
Homeworks	HW-RPM-4A-120	1 – 20 per output	3% - 100%	Max. 33 lamps per module Low-end trim available
	HRD-5ND, HWD-5NE	1 – 8	8% - 100%	Low-end trim available
Commercial Systems	LP-RPM-4A-120	1 – 20 per output	3% - 100%	Max. 33 lamps per module Low-end trim available
Interfaces	PHPM-WBX ⁽²⁾	1 – 34	2% - 100%	Low-end trim available
	PHPM-PA ⁽³⁾	1 – 34	2% - 100%	Low-end trim available

⁽¹⁾ Values are based on light output using the specified dimming control, and may not be an indication of the fixture's full capability.

⁽²⁾ Controlled with Ariadni, Diva, Lyneo Lx, Maestro, Nova, Nova T*, Skylark, or Vareo 3-Wire Fluorescent dimmers, or GrafikEye

⁽³⁾ Controlled with HomeWorks or Commercial Systems

Comments: The ability to set the low-end trim is available on select 3-Wire Fluorescent dimmers, Homeworks, and Commercial Systems products. Refer to product documentation or www.lutron.com for details.