


Lutron — Finiré 3" LED Recessed Lights: Ivalo® Collection

Job name: _____ Room: _____ Qty: _____


Step 1 Select Type of Recessed Light



Downlight




Adjustable




Infinite Adjustable

Step 2 Select Flange and Aperture




Round Trimmed




Square Trimmed



Square Pinhole Downlight




Round Pinhole Downlight



Round Pinhole (Slotted) Adjustable




Round Trimless




Square Trimless



Square Trimless Pinhole Downlight



Round Trimless Pinhole Downlight



Round Trimless Pinhole (Slotted) Adjustable

Step 3 Select LED Type

- 17 W 850lm, 97 CRI Standard
 17 W 1100lm, 97 CRI High Output

- 17 W 650lm, 97 CRI Narrow Spot
 29 W 1750lm, 97 CRI High Plus (Non-IC only)

Step 4 Select Housing

- Non-Insulation Contact
 13.6" L x 9.5" W x 4.9" H

- Insulation Contact
 18.9" L x 9.5" W x 6" H

Step 5 Select Color Temperature

- 2700K 3000K 3500K




Step 6 Select Beam Spread




15° Beam Spread
(Narrow Spot only)



28° Beam Spread



40° Beam Spread



60° Beam Spread

Step 7 Select Control Method

Residential

2-Wire, 120V~

Residential/Commercial

EcoSystem, 120/277V~

Fixtures were designed for ideal compatibility and performance with Lutron drivers and controls.

Step 8 Select Hanging Type

14-24" Adjustable Hanging Bars

9.5-15" Narrow Joist Hanger Bars

Step 9 Select Ceiling Thickness


Standard (1/2" - 5/8")

Thick Ceiling (5/8" to 2")

Trimless Wood/Stone (1/2" - 1 1/2")

Contact fixtures@lutron.com to provide custom ceiling thickness dimensions)

Step 10 Select Finish



Matte White



Matte Black



Silver



Bronze



Silver/White



Clear Anodized/White



Clear Chrome/White




Black Chrome/White


Step 11 Select Lens



Micro Prism Solite



Frosted



Wallwash



No Lens



www.lutron.com/ivalo

Lutron Electronics Co., Inc.
7200 Suter Road
Coopersburg, PA 18036-1299

Customer Service and 24/7 Technical Support
610.282.7472 or fixtures@lutron.com.

Please contact your local Lutron sales representative or fixtures@lutron.com for more information on ordering product.

The Lutron logo, the Sunburst logo, Lutron, Finiré, and Ivalo are trademarks of Lutron Electronics Co., Inc, registered in the U.S. and other countries.

Micro Prism Solite is a trademark of Lutron Electronics Co., Inc.



© 01/2019 Lutron Electronics Co., Inc. | P/N 368-4032 REV I